



NOTES:

1. TERMINAL TO BE USED IN HOUSING 70066-**** AND 70450-****.
2. REFER TO PRODUCT SPECIFICATION PS-70058.
3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
4. TERMINAL TO BE USED WITH (0.64)/.025 SQUARE PINS.
5. TERMINAL TO BE USED WITH 32-36 AWG STRANDED WIRE WITH (0.64)/.025 MAXIMUM DIAMETER INSULATION.
6. TERMINALS SUPPLIED IN REEL FORM.
7. CRIMP SIZE INDICATOR B=32-36 AWG

PLATING:

.000150 MINIMUM TIN PLATE IN SELECT AREA,
OVER NICKEL PLATE OVERALL.

REEL UNWIND DIR EC NO: UCP2013-5345 TIDRWHIPPLE 2013/06/11 CHKD:MORGAN 2013/06/11 APPR:SMILLER 2013/07/09 REV	DESCRIPTION	QUALITY SYMBOLS F=0 F=0 F=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 10:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION				
				mm	INCH	DRAWN BY RWHIPPLE	DATE 2013/06/11	TITLE TERMINAL - BOX/CRIMP FOR 32-36 AWG ON A REEL					
			4 PLACES	± ---	± ---	CHECKED BY JAS	DATE 1988/02/03						
			3 PLACES	± ---	± .005	APPROVED BY SMILLER		DATE 2013/07/09	DOCUMENT NO. SD-70058-0013				
			2 PLACES	± 0.13	± .01								
1 PLACE	± 0.25	± ---	MATERIAL NO. 16-02-0084		SHEET NO. 1 OF 1								
			0 PLACE	± ---	± ---	SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					
			ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS										