

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [19009-0018](#)  
**Status:** **Active**  
**Description:** VibraKrimp™ Quick Disconnect Flag, Female, for 14-16 AWG Wire, Metal Strip Carrier

**Documents:**  
[Drawing \(PDF\)](#) [Product Specification PS-19902-011 \(PDF\)](#)  
[Product Specification PS-19902-005 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

CSA LR18689  
UL E79133

**General**

Product Family Quick Disconnects  
Series [19009](#)  
Comments Wire Grip  
Crimp Quality Equipment Yes  
Insulated No  
Product Name VibraKrimp™  
Type Quick Disconnect  
UPC 800755046939

**Physical**

Barrel Type Closed  
Gender Female  
Glow-Wire Compliant No  
Insulation None  
Lock to Mating Part None  
Material - Metal Brass  
Material - Plating Mating Tin  
Material - Plating Termination Tin  
Net Weight 0.679/g  
Orientation Flag  
Packaging Type Reel  
Polarized to Mating Part No  
Tab Thickness 0.81mm  
Tab Width 4.75mm  
Temperature Range - Operating Per Wire Specification  
Wire Insulation Diameter 3.68mm  
Wire Size AWG 14, 16  
Wire Size mm² 1.30 - 2.00

**Electrical**


Voltage - Maximum Per Wire Specification

**Material Info**

Old Part Number BBZ-4171-032

**Reference - Drawing Numbers**

Product Specification PS-19902-005, PS-19902-011  
Sales Drawing CDFGS187



Series

image - Reference only

**EU RoHS**

**ELV and RoHS  
Compliant**  
**REACH SVHC**  
**Contains SVHC: No**  
**Low-Halogen Status**  
**Low-Halogen**

**China RoHS**



**Need more information on product  
environmental compliance?**  
  
Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of  
Compliance, [click here](#)  
  
Please visit the [Contact Us](#) section for any  
non-product compliance questions.

**Search Parts in this Series**  
[19009Series](#)

**Application Tooling | FAQ**  
*Tooling specifications and manuals are  
found by selecting the products below.  
Crimp Height Specifications are then  
contained in the Application Tooling  
Specification document.*  
**Global**

| Description                                                         | Product #                  |
|---------------------------------------------------------------------|----------------------------|
| ASP Perishable                                                      | <a href="#">0190290152</a> |
| Tool Kit used in ASP<br>presses that process<br>metal strip product |                            |
| Rear Feed Applicator                                                | <a href="#">0638027700</a> |
| for Quick Disconnect<br>Female Flag<br>Terminals, 14-16<br>AWG Wire |                            |