

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

19023-0014

Status:

Active

Description:

InsulKrimp™ Fully Insulated Quick Disconnect, Male, for 14-16 AWG (2.00-1.30mm²) Wire, Mylar Tape, Tab 6.35 x 0.81mm

Documents:

Drawing (PDF)

Product Specification PS-19902-008 (PDF)

Product Specification PS-19902-011 (PDF)

Product Specification PS-19902-015 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR18689

UL

E79133

General

Product Family

Quick Disconnects

Series

19023

Comments

Funnel Entry

Crimp Quality Equipment

Yes

Insulated

No

Product Name

InsulKrimp™

Type

Quick Disconnect

UPC

800753039957

Physical

Barrel Type

Closed

Color - Resin

Blue

Flammability

94V-0

Gender

Male

Glow-Wire Compliant

No

Insulation

PVC

Lock to Mating Part

None

Material - Metal

Brass

Material - Plating Mating

Zinc Chromate

Material - Plating Termination

Zinc Chromate

Material - Resin

PVC

Net Weight

1.136/g

Orientation

Straight

Packaging Type

Adhesive Tape on Reel

Polarized to Mating Part

No

Tab Thickness

0.81mm

Tab Width

6.35mm

Temperature Range - Operating

-50°C to +105°C

Wire Insulation Diameter

4.40mm max.

Wire Size AWG

14, 16

Wire Size mm²

1.30 - 2.00

Electrical

Voltage - Maximum

600V

Material Info

Old Part Number

MCT-2XT

Reference - Drawing Numbers

Product Specification

PS-19902-008, PS-19902-011, PS-19902-015

Sales Drawing

SD-19023-004




image - Reference only

Series

EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

19023Series

Use With

19005-0005

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Crimp Dies for MTA-100 Tape Applicator used in 3BF Press, MTA-105 Tape Applicator used in TM-2000™ Press, and ATP-301 Air Crimping Press for Mylar Tape Mounted Terminals

0192880085

This document was generated on 10/21/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**