





SUGGESTED PCB LAYOUT



SCHEMATIC



SPECIFICATIONS

FUNCTION:
1P3T ON-ON-ON

RATINGS:
0.5A 50VDC

CONTACT RESISTANCE:
Initial: 30mΩ Max.

INSULATION RESISTANCE:
500MΩ Min. at 500VDC

DIELECTRIC STRENGTH:
500VAC For 1 Minute

ELECTRICAL LIFE:
10,000 Cycles

APPROVALS:
RoHS LEAD FREE
COMPLIANT PROCESS COMPATIBLE

MATERIALS

BASE:
Phenolic Board

COVER:
Nickel Plated Steel

ACTUATOR:
Polyoxymethylene (POM)

CONTACT:
Silver Plated Brass

TERMINALS:
Silver Plated Brass

COLORS

ACTUATOR:
Black

LSS-130401B7			
DIMENSIONS INCHES [MILLIMETERS] GENERAL TOLERANCES ±0.008 [±0.2] / ±1°		DRAWING NUMBER 03-LSS130401B7	
SCALE DRAWING NOT TO SCALE		DATE SEPTEMBER 27, 2009	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED		REVISION A	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

A
REV.

INITIAL RELEASE
DESCRIPTION

PCRD0115
POR

09/09/27
DATE

CAB
DRAWN BY

SCALE
DRAWING NOT TO SCALE

PROJECTION
FIRST ANGLE

DRAWING NUMBER
03-LSS130401B7

DATE
SEPTEMBER 27, 2009

REVISION
A