



PACKAGING TYPE:
Tube

TUBE QUANTITY:
75 Pieces

POSITION 1
(MAINTAINED)

POSITION 2
(MOMENTARY)

FUNCTION:
1P1T OFF—(ON), Washable

RATINGS:
50mA 12VDC

OPERATING FORCE:
360±90gf

TRAVEL:
0.024±0.008 [0.6±0.2]

CONTACT RESISTANCE:
Initial: 100mΩ Max.

INSULATION RESISTANCE:
100MΩ Min. at 500VDC

DIELECTRIC STRENGTH:
250VAC For 1 Minute

ELECTRICAL LIFE:
500,000 Cycles

SHOCK RESISTANCE:
Mil—Std. 202F, Method 213B

VIBRATION RESISTANCE:
Mil—Std. 202F, Method 201A

TEMPERATURE:
Operating: -25°C to 70°C
Storage: -30°C to 80°C

RoHS COMPLIANT **LEAD FREE**
PROCESS COMPATIBLE

ACTUATOR:
Transparent

BASE:
Nylon Thermoplastic, UL94 V-0

COVER:
Stainless Steel

ACTUATOR:
Silicone Rubber

CONTACTS:
Stainless Steel

TERMINALS:
Silver Plated Brass

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

A	INITIAL RELEASE	PCR00108	09/09/14	CAB
REV.	DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS		INCHES [MILLIMETERS]	
GENERAL TOLERANCES		± 0.008 [± 0.2] / $\pm 1^\circ$	
SCALE	DRAWING NOT TO SCALE		PROJECTOR

