






SECTION A-A

NOTE

MATERIAL:

1. 1-1 HOUSING: LCP UL94V-0
- 1-2 CONTACT: 1~4PIN,COPPER(T=0.20MM)
5~9PIN,BTASS(T=0.20MM)
- 1-3 SHELL: FRONT SHELL,BRASS(T=0.30MM)
COVER SHELL,SPCC(T=0.20MM)

2.ELECTRICAL CHARACTERISTICS:



- 2.1 CONTACT RESISTANCE:30MOHM MAX.
- 2.2 CONTACT CURRENT RATING:1.5A
- 2.3 DIELECTRIC WITHSTANDING VOLTAGE:500 V R.M.S.
- 2.4 INSULATION RESISTANCE 1000 MEGOHMS MIN.
- 2.5 OPERATING TEMPERATURE:-40°C~85°C

3.MECHANICAL CHARACTERISTICS:


- 3.1 MATING FORCE:3.57KG MAX.
- 3.2 UNMATING FORCE:1.02KG MIN.
- 3.3 DURABILITY:MANDATORY:5000 CYCLES.

4.PLATING

- 4.1 TERMINAL:GOLD FLASH ALL OVER 50U"MIN
NICKEL AND 1U"MIN TIN ALL OVER 50U"MIN.
NICKEL ON SOLDER AREA
- 4.2 SHELL:150U" MIN.NICEL OVER 20U"MIN BRASS.



RECONNANDED PCB ALAYOUT

10/10/26	ING		NEW DWG		A0
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED		CnC Tech , LLC			
			TITLE: USB 3.0 B/F DIP90° 15U"		
X.X ±0.38	X.X° ±2°	APPD:	PRODUCT NO: 1003-024-02000		
X.XX ±0.25	X.XX° ±1°	CHECK:	DATE	SCALE	PAGE
X.XXX ±0.10	X.XXX° ±0.5°	DRAW:	2010.10.26	1:1	1 / 1