


## FED. MFG. CODE 01029

CATALOG LISTING

102TL200-1

 <b>CIRCUIT MADE WITH TOGGLE LEVER IN</b>		
<b>KEYWAY SIDE</b> (1-2,4-5)	<b>CENTER</b> (1-2,4-5)	<b>OPPOSITE KEYWAY</b> (2-3,5-6)

RESISTIVE LOAD					LAMP LOAD		INDUCTIVE LOAD	
DC VOLTS			AC VOLTS					
28	125	250	125	250	28 VDC	125 VAC	28 VDC	125 VAC

7.

Technical drawing of a rectangular component with dimensions and labels:

- Overall width: 1.32
- Overall height: .89
- Internal width segments: .38 (left), .38 (right)
- Internal height segments: .38 (top), .38 (bottom)
- Labels:
  - SEALED CONSTRUCTION (RED SEAL)
  - TERMINALS ACCEPT PIN M39029/1-101
- Symbol: A triangle containing the number 6.

- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- 2 - CIRCUIT DESIGNATION, MICRO SWITCH CATALOG LISTING, CUSTOMER PART NO. C10983-1, AND DATE CODE IDENTIFIED ON SIDE OF SWITCH
- 3 - FURNISHED UNASSEMBLED
- 4 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M83723/28-20
- 5 - APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS
- 6 - THE SEALING GROMMET SHALL SEAL ON A SMOOTH WIRE INSULATION OF .040 TO .083 DIAMETERS
- 7 - CONTACT TRANSFER OCCURS WHEN TOGGLE LEVER IS MOVED 8° MIN. FROM CENTER.

HEX NUT (2)

1

MAR 83

WEIGHT .119 LBS MAX