






HONEYWELL
PART NUMBER
102TL2887 SERIES CHART 1


REV	DOCUMENT	CHANGED BY	CHECK
5	0008691	KSR 25OCT04	AK
6	0009174	KR 22NOV04	AK



- NOTES
- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
 - 2 - CIRCUIT DESIGNATION AND MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH
 - 3 - FURNISHED UNASSEMBLED
 - 4 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M83723/28-20
 - 5 - APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS
 - 6 - THE SEALING GROMMET SHALL SEAL ON A SMOOTH WIRE INSULATION OF ϕ .040 - .083
 - 7 - GOLD PLATED CONTACTS
 - 8 - FROM BOTTOM OF KEYWAY TO MAJOR ϕ OF 15/32 THREAD
 - 9 - FAA-PMA TO BE MARKED ON THESE SWITCHES
 - 10 - FOR MANUFACTURING DETAIL SEE THE CORRESPONDING ASSEMBLY DRAWING FOR EACH LISTING FOR FAA-PMA

ELECTRICAL RATING	FAA-PMA APPROVED 9 10	CATALOG LISTING	5 CIRCUIT MADE WITH TOGGLE LEVER IN		
			KEYWAY SIDE (1-2, 4-5)	CENTER (1-2, 4-5)	OPPOSITE KEYWAY (2-3, 5-6)
.1A 28 VDC, 115 VAC		102TL2887-1	ON	OFF	ON
		102TL2887-2	OFF	NONE	ON
	FAA-PMA	102TL2887-3	ON	NONE	ON
		102TL2887-4	MOM OFF	NONE	ON
		102TL2887-5	MOM ON	OFF	ON
		102TL2887-6	MOM ON	NONE	OFF
		102TL2887-7	MOM ON	OFF	MOM ON
		102TL2887-8	MOM ON	NONE	ON
		102TL2887-21	NONE	OFF	ON
		102TL2887-31	NONE	ON	ON
		102TL2887-51	NONE	ON	MOM ON
		102TL2887-61	MOM ON	OFF	NONE



DESIGN UNITS: INCH TOLERANCES UNLESS NOTED:				DRAWN	KSR	25OCT04
				CHECK	AK	25OCT04
NO PLACE	X	±	0.040	THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		
ONE PLACE	.X	±	0.030			
TWO PLACE	.XX	±	0.015			
THREE PLACE	.XXX	±	0.005			
FOUR PLACE	.XXXX	±	0.0005			
ANGLES		±	2	INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY		
THIRD ANGLE PROJECTION						
				RASTER		

Honeywell				
TITLE				
SWITCH - TOGGLE				
SIZE	TYPE	DRAWING NAME		REV
B	I	102TL2887 SERIES CHART 1		6
SCALE	1 : 1	WEIGHT .119 LB MAX	SHEET	1 OF 1