


M



1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD

3 KEYWAY SHOWN ON LEFT SIDE


5 THE SEALING GROMMET S

6 SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE

7 - UNUSED TERMINAL HOLES MAY BE SEALED WITH PLUGS M83



"A" LOCKED IN THREE POSITIONS	"B" LOCKED IN CENTER AND EXTREME POSN (KEYWAY SIDE)	"D" LOCKED OUT OF CENTER POSITION	"E" LOCKED IN CENTER POSITION	"F" LOCKED IN EXTREME POSN (OPP KEYWAY)	"G" LOCKED IN EXTREME POSN (KEYWAY SIDE)
"H" LOCKED OUT OF CENTER AND EXTREME POSN (KEYWAY SIDE)	"J" LOCKED OUT OF CENTER AND EXTREME POSN (OPP KEYWAY)	"K" LOCKED IN CENTER AND EXTREME POSN (OPP KEYWAY)	"I" LOCKED OUT OF EXTREME POSN (KEYWAY SIDE)	"M" LOCKED OUT OF AND INTO EXTREME POSN	"N" LOCKED OUT OF EXTREME POSN (OPP KEYWAY)

 LOCKWASHER 	 LOCKING RING 	 2X HEX NUT 
---	---	---

CIRCUIT MADE WITH TOGGLE LEVER IN		
KEYWAY SIDE	CENTER	OPPOSITE KEYWAY
MAINTAINED POSITION	MAINTAINED POSITION	MAINTAINED POSITION

SCALE	FULL
-------	------

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) $\pm .030$

TWO PLACES (.00) $\pm .015$

THREE PLACES (.000) $\pm .005$ ANGLES +

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

MICRO SWITCH
a Honeywell Division

FED MEG CODE 91939

SWITCH-TOGGLE

CATALOG LISTING
104TL1-111 SERIES
CHART 1

MASTER REDUCED
ANSI Y14.5M-1982 APPLIES

104TL1-111 SERIES
CHART 1

DRAWING
NUMBER

1	
2	

REVISIONS

PTC / CAD 2D
DRAWN