

HONEYWELL
PART NUMBER



11SM7601-H4

PRODUCT CODE

TWZ4500

REV	DOCUMENT	CHANGED BY	CHECK
9	0041782	PK 21JUL08	ASD

PLASTIC PLUNGER



NOTE -

- 1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .087 MAX DIA ON .375 ± .002 CENTERS
- 2 - TERMINALS ARE PLATED FOR SOLDERING
- 3 - SWITCH WILL WITHSTAND TEMPERATURE OF 250° F

RELEASE NO.
PR - 3414

REPLACES
-

CHARACTERISTICS

OPERATING FORCE - - 56 GRAM MAX

RELEASE FORCE - - - - 14 GRAM MIN

DIFFERENTIAL TRAVEL - - - .002 MAX

OVERTRAVEL - - - - - .005 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
SPDT

30 VOLTS DC RATING

	SEA LEVEL	50,000 FT
INDUCTIVE	3 AMP	2.5 AMP
RESISTIVE	5 AMP	5 AMP

MAXIMUM INRUSH 24 AMP

APPROVALS	UL, CSA	4A 250 VAC 1/10 HP 125 VAC	UL	CS	BRAND L185
-----------	---------	-------------------------------	----	----	---------------

DESIGN UNITS: INCH

TOLERANCES UNLESS NOTED:

NO PLACE	X	±
ONE PLACE	.X	±
TWO PLACE	.XX	±
THREE PLACE	.XXX	±
FOUR PLACE	.XXXX	±
ANGLES		±

THIRD ANGLE PROJECTION



DRAWN

VK

15 FEB 08

CHECK

RJ

15 FEB 08

THIS DRAWING COVERS A PROPRIETARY ITEM
AND IS THE PROPERTY OF HONEYWELL.
THIS DRAWING IS NOT TO BE COPIED OR USED
WITHOUT THE PERMISSION OF HONEYWELL.

INTERPRET PER ANSI Y14.5M-1982
OTHER HONEYWELL ENGINEERING
STANDARDS MAY APPLY

RASTER

Honeywell

TITLE

SWITCH - BASIC

SIZE

B

TYPE

I

DRAWING NAME

11SM7601-H4

REV

9

SCALE

-

WEIGHT .006 LB MAX

SHEET 1 OF 1