

**Ethernet Switch****Ha-VIS mCon 4080-BPoE1V**

8-port Ethernet Switch for flat installation

Managed	IP 40	PROFINET compatible	EtherNet/IP compatible
---------	-------	---------------------	------------------------

Number of ports, Copper / Termination	8x 10/100Base-T(X) / M12 D-coding (female)
mode PoE	
Input voltage / Termination	48 V DC
Permissible range (min./max.)	46 V ... 55 V DC
Input current	max. 3.0 A at 48 V DC with PoE; load 350 mA each port
mode Non-PoE	
Input voltage / Termination	24 / 48 V DC / M12 A-coding, male, for redundant power supply
Permissible range (min./max.)	12 V ... 55 V DC
Input current	approx. 350 mA (at 24 V DC)
Housing material	metal, powder-coated
Dimensions (W x H x D)	130 x 166 x 50 mm (without connectors)
Weight	approx. 0.85 kg
Working temperature	-40 °C ... +70 °C
MTBF	296.000 h
Management	fully managed via Web interface and SNMP Functions see page A-9

Identification	Part number	Drawing	Dimensions in mm
Ha-VIS mCon 4080-BPoE1V Ethernet Switch with 8 ports M12 D-coding for wall mounting	20 77 208 4009		