



Ethernet Switch
Ha-VIS mCon 9080-B1V
 8-port Ethernet Switch for installation in a 19" rack

Managed	IP 20	PROFINET compatible <input checked="" type="checkbox"/>	EtherNet/IP compatible <input checked="" type="checkbox"/>
---------	-------	---	--

Number of ports, Copper / Termination	8x 10/100Base-T(X) / M12 D-coding (female)
Input voltage / Termination	24 / 48 V DC / DIN frame connector, Type F
Permissible range (min./max.)	8 V ... 60 V DC
Input current	approx. 130 mA (at 24 V DC)
Alarm signalling contact	Change-over contact, potential-free, 24 V DC / 0.5 A DIN frame connector, Type F
Housing material	aluminium, anodised
Dimensions (W x H x D)	60.6 mm (3 U) x 128.4 mm (12 HP) x 173.5 mm
Weight	approx. 0.6 kg
Working temperature	-40 °C ... +70 °C
Approvals	cUL (in preparation)
MTBF	631.000 h
Management	fully managed via Web interface and SNMP Functions see page A-9

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS mCon 9080-B1V
 Ethernet Switch with
 8 ports M12 D-coding

20 76 208 7002

