

**MICRO SWITCH**

FREEPORT ILLINOIS, U.S.A

A DIVISION OF HONEYWELL INC.

FED. MFG. CODE 91929

**SWITCH - BASIC**

CATALOG LISTING

**12BS214****12BS214****M**DRAWING  
NUMBER**X2**

ISSUE

REPLACES X81344-12BS

RELEASE NO. PR-13968

CHECK

REVISIONS

A 80-73267-0  
J A  
20 OCT 93

CHECK

CHECK

CHECK

CHECK

CHECK

CHECK

CHECK


CHECK

3X 8-32 UNC (.219) BINDING  
HEAD COMBINATION TERMINAL  
SCREW AND CUPWASHER**NOTES**

- △ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000±.002 CENTERS  
2 - ADJUSTING SCREW BUSHING IS AT SAME ELECTRICAL POTENTIAL AS NORMALLY CLOSED TERMINALS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

**CHARACTERISTICS**

OPERATING FORCE----- 25 OZ MAX

RELEASE FORCE----- 4 OZ MIN

OVERTRAVEL----- .005 MIN

**ELECTRICAL DATA**CONTACT ARRANGEMENT  
S P D TL111  
15A 125, 250 OR 277 VAC  
1/8 HP 125 VAC, 1/4 HP 250 VAC**SCALE FULL****DO NOT  
SCALE PRINT**UNLESS OTHERWISE SPECIFIED  
TOLERANCES ARE

ONE PLACE (.0) ± .030

TWO PLACE (.00) ± .015

THREE PLACE (.000) ± .005

ANGLES ±

RAW MATERIAL - COMMERCIAL STANDARD

DIMENSIONS ARE IN INCHES AND ARE  
TO BE MET BEFORE PROTECTIVE  
COATINGS ARE APPLIED

MICRO SWITCH STANDARDS APPLY

**WEIGHT**

FD-52948-B

DRAWN

JAS 12 JUNE 85