


**SPECIFICATIONS**

FUNCTION:
1P1T OFF-ON

RATINGS:
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):
16A 125VAC [cULus]
16A 250VAC [cULus]
CAN/CSA C22.2 No. 55 (233821):
16A 125VAC [CSA]
16A 250VAC [CSA]

DIN 61058-1/VDE 0630-1:2008-09 and EN 61058-1:2002+42:2008 (40011301):
16(6)A 250~ 1E4 T125/55 [VDE]

CONTACT RESISTANCE:
Initial: 20mΩ Max.

INSULATION RESISTANCE:
100MΩ Min. at 500VDC

DIELECTRIC STRENGTH:
1,000VAC for 1 Minute

ELECTRICAL LIFE:
6,000 Cycles [cULus, CSA]
10,000 Cycles [VDE]

TEMPERATURE:
Operating: -20°C to 85°C [cULus, CSA]
Operating: -20°C to 125°C [VDE]

OPERATING FORCE:
500±200gf

APPROVALS:**MATERIALS**


ACTUATOR:
Polybutylene Terephthalate (PBT), UL94 V-2

BODY:
Polyamide 6/6 (PA66), UL94 V-2

BASE:
Polybutylene Terephthalate (PBT), UL94 V-2

CONTACTS:
Silver Alloy

TERMINALS:
Silver Plated Copper

SUGGESTED PCB LAYOUT

ACTUATOR	A	09/06/20	CAB
BODY	A	09/06/20	CAB
MATERIALS	A	09/06/20	CAB
SPECIFICATIONS	A	09/06/20	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED

REV.

Release to Production
DESCRIPTION

REV.

DATE

DRAWN BY

SCALE

DRAWING NOT TO SCALE

PROJECTION

ITEM NUMBER

DATE

REVISION



E-SWITCH



LAMB INDUSTRIES

PASFC31J

SEPTEMBER 01, 2011

A