



LOCKWASHER

AVAILABLE

LOCKING

COMBINATIONS

FOR CONFIGURATION

SEE LETTERED

DETAILS

CENTER AND

EXTREME POS

KEYWAY SIDE

OCKED OUT OF

CENTER AND

(OPP. KEYWAY) (OPP. KEYWAY

EXTREME POS.

CATALOG

LISTING

14NT1-

14NT1-

14NT1-3

14NT1-21

14NT1-31

14NT1-4

14NT1-5

14NT1-6

14NT1-7

14NT1-8

14NT1-51

14NT1-61

LOCKED IN

POSITIONS

OCKED OUT OF CENTER AND

EXTREME POS

(KEYWAY SIDE)

LOCKED OUT OF

AND INTO EXTREME POS (KEYWAY SIDE

THREE

.05 . 040 -LOCKING RING

WITH TOGGLE IN

CENTER

1-2, 4-5,

7-8, 10-11

OFF

NONE

NONE

OFF

ON

NONE

OFF

NONE

OFF

NONE

ON

OPPOSI

KEYWAY

2-3, 5-6

3-9, 11-1

ON

ON

ON

ON

ON

ON

ON

OFF

MOM ON

ON

MOM (

NONE

LOCKED IN

CENTER POSITION

OCKED OUT OF

EXTREME POS.

(KEYWAY SIDE)

KEYWAY

SIDE

1-2, 4-5

7-8, 10-1

ON

OFF

ON

NONE

NONE

MOM OF

MOM ON

MOM ON

LOCKED OUT

OF CENTER

POSITION

LOCKED IN

CENTER AND

EXTREME POS

14NT1 SERIES CHART

ELECTRICAL DATA

L191 15A 125, <u>250</u>, 277 VAC 1/2HP 125 VAC 1HP <u>250</u>, 277 VAC 5A 125 VAC "L"

L¹⁹² 10A 125, <u>250</u>, 277 VAC

LOCKED IN

EXTREME POS.

(OPP. KEYWAY)

OCKED OUT OF

EXTREME POS.

(OPP. KEYWAY)

AND INTO

1/4HP 125 VAC

1/2HP <u>250</u>, 277 VAC **3** 125 VAC "L"

A1 (1)

71 @

EXTREME POS

(KEYWAY SIDE)

OCKED OUT OF

EXTREME POS.

(OPP. KEYWAY)

2X HEX NUT 3

1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD

2 - MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH

/3\ FURNISHED UNASSEMBLED

APPLIES ONLY TO "ON" AND "MOM ON" POSITION

SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE TOGGLE LOCKING,

SEE CHART FOR AVAILABLE LOCKING COMBINATIONS

KEYWAY SHOWN ON LEFT SIDE

FROM BOTTOM KEYWAY TO MAJOR \emptyset OF 15/32 THREAD

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH. A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

MICRO SWITCH a Honeywell Division

SWITCH - TOGGLE

14NT1 SERIES CHART

CATALOG LISTING

TWO PLACES (.00) ±.015 THREE PLACES (.000) ± .005

ONE PLACE (.0) $\pm .030$

THIRD ANGLE PROJECTION ⊕ -=-]-

DO NOT SCALE PRINT UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ANGLES WEIGHT

ANSI Y14.5M-1982 APPLIES

FED. MFG. CODE 91929

7

14NT1 SERIES CHART

DR AW I NG NUMBER

က

A CO-94328 S A V 22 NOV 99 B 0006142