

Product Configuration System



Real Time Clock Modules – Serial (3 Wire & 4 Wire)

RX-4571SA

:

B

0

:

PURE SN

Base Model	Pkg.
RTC-4574NB	SON 22 PIN
RX-4045NB	SON 22 PIN
RX-4045SA	SOP 14 PIN
RX-4574LC	VSOJ 12 PIN
RX-4575LC	VSOJ 12 PIN
RX-4571LC	VSOJ 12 PIN
RX-4571NB	SON 22 PIN
RX-4571SA	SOP 14 PIN
RX-4801SA	SOP 14 PIN
RX-4803SA	SOP 14 PIN
RX-4803LC	VSOJ 12 PIN

Frequency Tolerance (Ta =+25 °C):	
RTC-4574NB	B=5+/-23PPM
RX-4045NB, RX-4045SA	AA=5+/-5PPM AC=0+/-5PPM
RX-4574LC	B=5+/-23PPM
RX-4575LC	B=5+/-23PPM
RX-4571LC	B=5+/-23PPM
RX-4571NB	B=5+/-23PPM
RX-4571SA	B=5+/-23PPM
RX-4801SA	Over -40 to +85 °C UB=+/-5PPM
RX-4803SA, RX-4803LC	Over -40 to +85 °C UA=+/-3.4PPM UB=+/-5PPM

Tape & Reel Qty
SOP Package Type Only
 Blank: Bulk
 0: 1000 pcs. per reel
 3: 250 pcs. per reel
DIP Package Type Only
 S: 25pcs/Stick

PURE SN
 Blank : Already RoHS Compliant

EPSON

Note:
 All LC packages are already RoHS Compliant with “PURE SN”
 *RX-4575LC - Sn-Ag Plating NOT PURE SN