





Top View of Assembly





SECTION A-A End View of Assembly



Top View Looking Inside Box



SECTION B-B Side View of Assembly



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

NOTE

Purchased assembly includes box, lid and 4 cover screws.
Box and lid are made from Diecast Aluminum Alloy.
Silicone Gasket supplied with liquid resistant enclosure.
Bottom Flange is Welded.

PART NUMBERS

1590KKF Enclosure	
Natural Finish Enclosure	1590KKF
Black Textured Enclosure	1590KKFBK
1590KKF Liquid Resistant Enclosure (Silicone Gasket)	
Natural Finish Enclosure	1590WKKF
Black Textured Enclosure	1590WKKFBK

ACCESSORIES

Recommended Torque: 75 ozf.in / 55 cN.m

Liquid Resistant Cover Screws

Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100
Black Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring]	1590WMS100BK

Standard Cover Screws

Plated Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100
Black Cover Screws (Pkg 100) [6-32 x 1/2"]	1590MS100BK

HAMMOND
MANUFACTURING™
1590KKF
www.hammondmfg.com

Dimensions:
mm
[inches]