Product Configuration System

Crystal Oscillators - Programmable

SG-8003 | JF | 32.0000M | - | P | E | C | L0 | : | PURE SN

Model Number

Package Type
CA: Ceramic 7.0x5.0mm (SG-710 Type)
CE : Ceramic 3.2x2.5mm (SG-310 Type)
CG: Ceramic 2.5 x 2.0 (SG-210 Type)
JF: Plastic 7.1x5.1mm (SG-645 Type)
LB: NPO 5.0x3.2mm (SG-550 Type)

Output Frequency
1.0000 ~ 166.0000MHz:
M: Unit in MHz

Function
P: OE
S: ST

Power Supply
E: 1.8V, CMOS (50% VCC)
D: 2.5V, CMOS (50% VCC)
C: 3.3V, CMOS (50% VCC)

Frequency Stability / Op Temp
B: +/-50ppm -20˚ ~ +70˚C
C: +/-100ppm -20˚ ~ +70˚C
L: +/-50ppm -40 ˚ ~ +85˚C
M: +/-100ppm -40˚ ~ +85˚C

Packaging
Tape and Reel
L0: 1000pcs per reel
L3: 250pcs per reel
L6: 2000pcs per reel
B: Bulk

SG-8003JF Only
PURE SN
Blank = RoHs Compliant

EPSON