

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		
CHARACTERISTICS	ELECTRICAL DATA	SCALE 1/2 TO 1
OPERATING TORQUE - - - - 1.7 IN-LB MAX	CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)	DO NOT SCALE PRINT
FULL OVERTRAVEL TORQUE- - 2.25 IN-LB MAX		UNLESS OTHERWISE NOTED
RELEASE TORQUE - - - - .28 IN-LB MAX	10A-120, 240, OR 480 VAC, 1/3 HP - 120 VAC	DIMENSIONS ARE IN INCHES
PRETRAVEL - - - - -20° MAX	3/4 HP - 240 VAC; 0.8 A - 115 VDC; 0.4 A - 230 VDC	TOLERANCES ARE:
DIFFERENTIAL TRAVEL - - - - 12° MAX	.1A - 550 VDC	ONE PLACE (.0) ±.030
OVERTRAVEL - - - - - 30° MIN	PILOT DUTY: 600 VAC MAX	TWO PLACE (.00) ±.015
RELEASE TRAVEL - - - - - 5° MIN		THREE PLACE (.000) ±.005
SWITCH-BASIC REPLACEMENT - - - - 2MNG		ANGLES ±
		WEIGHT