


Number of contacts

9–37



Insulation displacement termination

	Identification	No. of contacts	Part No.	
D-Sub	Performance levels Explanations see page 05.04 Other performance levels on request		Performance level 3	
	Male connector²⁾ pitch 1.27 mm metal shell with dimples	9 15 25 37	09 66 128 770 . 09 66 228 770 . 09 66 328 770 . 09 66 428 770 .	Performance level 2 09 66 128 670 . 09 66 228 670 . 09 66 328 670 . 09 66 428 670 .
	Female connector²⁾ pitch 1.27 mm metal shell	9 15 25 37	09 66 118 750 . 09 66 218 750 . 09 66 318 750 . 09 66 418 750 .	09 66 118 650 . 09 66 218 650 . 09 66 318 650 . 09 66 418 650 .
	Please insert digit for flange thread ø 3.1 mm hole ▶ 0 M3 ▶ 1 ¹⁾ 4-40 UNC ▶ 2			
	Strain relief clamp plastic for male and female connector	9 15 25 37	09 66 108 0001 09 66 208 0001 09 66 308 0001 09 66 408 0001	09 66 108 0001 09 66 208 0001 09 66 308 0001 09 66 408 0001

¹⁾ Not normally kept in stock²⁾ Not released for halogen free flat cables