

CATALOG LISTING

2NT1-12 SERIES CHART 1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

ELECTRICAL RATING

15A 125, 250, 277 VAC
1/2HP 125 VAC
1HP 250, 277 VAC
5A 125 VAC "L"



2

LOCKED IN
EXTREME POS.
(KEYWAY SIDE)

LOCKED OUT OF
EXTREME POS.
(OPP. KEYWAY)

THE KEYW

OPPOSITE KEYWAY

MAINTAINED POSITION

LOCKING RING $\triangle 3$ LOCKWASHER $\triangle 3$

2X HEX NUT $\triangle 3$

1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD

2 - MICRO SWITCH CAT. LIST. MARKED ON SIDE OF SWITCH

3 - FURNISHED UNASSEMBLED

4 - KEYWAY SHOWN ON LEFT SIDE

5 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) $\pm .030$

TWO PLACE (.00) +.015

THREE PLACE (000) $\pm$ 0.05

THREE-PEACE	(1.000)	1.000
ANGLES		†

ANGLÉS	1

PTC	DF
-----	----

SAV

Technical drawing of a rectangular plate with a central circular feature and four corner holes. Dimension lines indicate a width of $.076 \pm .008$ for the central feature and a diameter of $.427$ for the corner holes.

Technical drawing of a binding head terminal assembly. The drawing shows a cross-section of the assembly with various dimensions and callouts.

Dimensions:

- Overall height: 1.35
- Height of the top section: .67
- Height of the middle section: .47
- Height of the bottom section: 1.10
- Width of the top section: .24
- Width of the middle section: .130 MIN
- Width of the bottom section: .250
- Width of the base: .130 MIN

Callouts:

- 15/32-32 UNS-2A THREAD TO WITHIN .060 OF SHOULDER
- SEALED TO PREVENT ENTRANCE OF LIQUIDS OR DUST
- 6X 6-32 UNC-2 X (.260) BINDING HEAD TERMINAL SCREW AND LOCKWASHER

—SEALED TO PREVENT ENTRANCE
OF LIQUIDS OR DUST

— 6X 6-32 UNC-2 X (.260)
BINDING HEAD TERMINAL
SCREW AND LOCKWASHER
(SEMS) 

Technical drawing of a Style 2 Lever. The drawing shows a side view of the lever with a curved top and a rectangular base. Key dimensions and angles are indicated:

- Top Angle:** $34^{\circ} \pm 8^{\circ}$
- Bottom Angle:** $17^{\circ} \pm 4^{\circ}$
- Total Travel:** Indicated by a horizontal dimension line at the top.
- Width:** $\phi .42$ (indicated by a horizontal dimension line on the right).
- Height:** 1.05 (indicated by a vertical dimension line on the left).
- Feature:** $.090$ APPROX PULLOUT TO CHANGE POSITION (indicated by a small horizontal dimension line on the left).

STYLE 2 LEVER

ANSI Y14.5M-1982 APPLIES