

MICRO SWITCH
a Honeywell Division
FED. MFG. CODE 91929

SWITCH - TOGGLE


2NT91-10 SERIES CHART 1

CATALOG LISTING

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CATALOG LISTING	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS	STYLE NUMBER	ELECTRICAL RATING	
			L191	15A 125, <u>250</u> , 277 VAC 1/2HP 125 VAC 1HP <u>250</u> , 277 VAC 5A 125 VAC "L"
2NT91-10	NONE	1		
2NT91-10/5	A,B,D,E,F,G,H,J,K,L,M,N,P	2		

.076±.008 WIDE KEYWAY



.427

STYLE 1 LEVER

17°±4°
34°±8° TOTAL TRAVEL

Ø .240



15/32-32 UNS-2A THREAD TO WITHIN .060 OF SHOULDER

SEALED TO PREVENT ENTRANCE OF LIQUIDS OR DUST











6X .250 WIDE QUICK CONNECT TERMINAL




NOTES


- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- 2 - MICRO SWITCH CAT. LIST. MARKED ON SIDE OF SWITCH
- 3 - FURNISHED UNASSEMBLED
- 4 - KEYWAY SHOWN ON LEFT SIDE
- 5 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS
- 6 - FOR TERMINAL COVER SEE MICRO SWITCH CAT. LIST. 5PA8



STYLE 2 LEVER

"A"	"B"	"D"	"E"	"F"	"G"
 LOCKED IN THREE POSITIONS	 LOCKED IN CENTER AND EXTREME POS. (KEYWAY SIDE)	 LOCKED OUT OF CENTER POSITION	 LOCKED IN CENTER POSITION	 LOCKED IN EXTREME POS. (OPP. KEYWAY)	 LOCKED IN EXTREME POS. (KEYWAY SIDE)
"H"	"J"	"K"	"L"	"M"	"N"
 LOCKED OUT OF CENTER AND EXTREME POS. (KEYWAY SIDE)	 LOCKED OUT OF CENTER AND EXTREME POS. (OPP. KEYWAY)	 LOCKED IN CENTER AND EXTREME POS. (OPP. KEYWAY)	 LOCKED OUT OF EXTREME POS. (KEYWAY SIDE)	 LOCKED OUT OF AND INTO EXTREME POS. (OPP. KEYWAY)	 LOCKED OUT OF EXTREME POS. (OPP. KEYWAY)
"P"	CIRCUIT MADE WITH TOGGLE LEVER IN				
 LOCKED OUT OF AND INTO EXTREME POS. (KEYWAY SIDE)	KEYWAY SIDE		CENTER		OPPOSITE KEYWAY
					
	MAINTAINED POSITION		MAINTAINED POSITION		MAINTAINED POSITION



THIRD ANGLE PROJECTION	
	
SCALE	FULL
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.0) ±.030
TWO PLACE	(.00) ±.015
THREE PLACE	(.000) ±.005
ANGLES	±
WEIGHT	.15 LBS APPROX