

MICRO SWITCH

FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-TOGGLE

CATALOG LISTING
2TL95 SERIES
CHART 1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CATALOG LISTING


CIRCUIT MADE WITH TOGGLE LEVER IN
KEYWAY SIDE (1-2,4-5) CENTER (1-2,4-5) OPPOSITE KEYWAY (2-3,5-6)

MILITARY RATING (AMPS)

RESISTIVE LOAD DC VOLTS AC VOLTS LAMP LOAD 28 VDC 125 VAC 28 VDC 125 VAC INDUCTIVE LOAD 28 VDC 125 VAC

CATALOG LISTING	KEYWAY SIDE (1-2,4-5)	CENTER (1-2,4-5)	OPPOSITE KEYWAY (2-3,5-6)	28	125	250	125	250	28 VDC	125 VAC	28 VDC	125 VAC
2TL95-1	ON	OFF	ON									
2TL95-2	OFF	NONE	ON									
2TL95-3	ON	NONE	ON	20	.75	.5	15	6	7	4	15	15
2TL95-21	NONE	OFF	ON	(REFER TO LI91 FOR UL RATING)								
2TL95-31	NONE	ON	ON									
2TL95-4	MOM OFF	NONE	ON									
2TL95-5	MOM ON	OFF	ON									
2TL95-6	MOM ON	NONE	OFF									
2TL95-7	MOM ON	OFF	MOM ON	18	.75	.5	11	6	5	2	10	8
2TL95-8	MOM ON	NONE	ON	(REFER TO LI92 FOR UL RATING)								
2TL95-51	NONE	ON	MOM ON									
2TL95-61	MOM ON	OFF	NONE									

.078±.008 WIDE KEYWAY



.427

34°±8°
TOTAL TRAVEL

17°±4°

10-32 UNF-2A THREAD

SEALED TO PREVENT ENTRANCE OF LIQUIDS OR DUST

15/32 UNS-2 THREAD TO WITHIN .060 OF SHOULDER

.68

.47

.24

1.10

1.653±.030

.130 MIN

.250 WIDE QUICK CONNECT TERMINAL (6)

1.340 MAX

.28

.75

.38

.26

.910 MAX

.38

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE (.0) ±.030
TWO PLACE (.00) ±.015
THREE PLACE (.000) ±.005
ANGLES


WEIGHT .20 LBS MAX

15A-125, 250 OR 277 VAC
1/2HP-125VAC; 1HP-250, 277VAC
5A-125VAC "L" CODE LI91


10A-125, 250, 277 VAC
1/4HP-125VAC; 1/2HP-250, 277VAC
3A-125VAC "L" CODE LI92

NOTES


- SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- CIRCUIT DESIGNATION AND MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH
- FURNISHED UNASSEMBLED
- FOR TERMINAL COVER SEE MICRO SWITCH CATALOG LISTING 5PA8
- APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS



LOCKWASHER



LOCKING RING



HEX NUT (2)