

REV	DOCUMENT	CHANGED BY	CHECK
4	0038558	SS 08MAY08	BLR



① MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF
 $\varnothing.087$ MAX ON $.188 \pm .002$ CENTERS
 2 - TERMINALS ARE PLATED FOR SOLDERING
 3 - SWITCH WILL WITHSTAND TEMPERATURE OF 250°F
 ④ CHARACTERISTICS ARE TAKEN AT POINT "A"

RELEASE NO.	PR-21210
REPLACES	X96072-SX

CHARACTERISTICS <u>A</u>		ELECTRICAL DATA				DESIGN UNITS: INCH TOLERANCES UNLESS NOTED: NO PLACE X ± ONE PLACE .X ± 0.030 TWO PLACE .XX ± 0.015 THREE PLACE .XXX ± 0.005 FOUR PLACE .XXXX ± ANGLES ±				DRAWN	SPK	26FEB08		Honeywell					
OPERATING FORCE — — 60 GRAMS MAX		CONTACT ARRANGEMENT SPDT								CHECK	RJ	26FEB08							
RELEASE FORCE— — — 11 GRAMS MIN			28 VOLTS DC RATING		115 VOLTS AC, 60 CPS			THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.						TITLE SWITCH - BASIC					
DIFFERENTIAL TRAVEL— — .015 MAX			SEA LEVEL	50,000 FT	SEA LEVEL														
OVERTRAVEL — — — — — .010 MIN		INDUCTIVE	3 AMP	2 AMP	5 AMP														
		RESISTIVE	5 AMP	4 AMP	5 AMP														
		-						INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY				SIZE	TYPE	DRAWING NAME		REV			
		APPROVALS	KEMA, CE	5A 250 V ~ T125	5E4								BRAND	L4L	B	I	311SX4-H391		4
								THIRD ANGLE PROJECTION 				RASTER			SCALE	-	WEIGHT:.003 LB MAX	SHEET 1 OF 1	