

ELECTRICAL DATA














L191 15A 125, 250, 277 VAC
1/2HP 125 VAC
1HP 250, 277 VAC
5A 125 VAC "I"



L192 10A 125, 250, 277 VAC
1/4HP 125 VAC
1/2HP 250, 277 VAC
3A 125 VAC "I"



CATALOG LISTING 4	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS	CIRCUIT MADE WITH TOGGLE LEVER IN 5		
		KEYWAY SIDE (1-2)	CENTER (1-2)	OPPOSITE KEYWAY (2-3, 5-6)
32NT291-1	A,B,D,E,F,G,H,J,K,L,M,N,P	ON	OFF	ON
32NT291-2	D,F,G	OFF	NONE	ON
32NT291-3	D,F,G	ON	NONE	ON
32NT291-21	E,F,K,M	NONE	OFF	ON
32NT291-31	E,F,K,M	NONE	ON	ON
32NT291-4	F	MOM OFF	NONE	ON
32NT291-5	E,F,K,L,M,N	MOM ON	OFF	ON
32NT291-6	F	MOM ON	NONE	OFF
32NT291-7	E,L,N	MOM ON	OFF	MOM ON
32NT291-8	F	MOM ON	NONE	ON
32NT291-51	E	NONE	ON	MOM ON
32NT291-61	F	MOM ON	OFF	NONE

LOCKED IN THREE POSITIONS	LOCKED IN CENTER AND EXTREME POS. (KEYWAY SIDE)	LOCKED OUT OF CENTER POSITION	LOCKED IN CENTER POSITION	LOCKED IN EXTREME POS. (OPP. KEYWAY)	LOCKED IN EXTREME POS. (KEYWAY SIDE)
<p>"A"</p>  <p>LOCKED IN THREE POSITIONS</p>	<p>"B"</p>  <p>LOCKED IN CENTER AND EXTREME POS. (KEYWAY SIDE)</p>	<p>"D"</p>  <p>LOCKED OUT OF CENTER POSITION</p>	<p>"E"</p>  <p>LOCKED IN CENTER POSITION</p>	<p>"F"</p>  <p>LOCKED IN EXTREME POS. (OPP. KEYWAY)</p>	<p>"G"</p>  <p>LOCKED IN EXTREME POS. (KEYWAY SIDE)</p>
<p>"H"</p>  <p>LOCKED OUT OF CENTER AND EXTREME POS. (KEYWAY SIDE)</p>	<p>"J"</p>  <p>LOCKED OUT OF CENTER AND EXTREME POS. (OPP. KEYWAY)</p>	<p>"K"</p>  <p>LOCKED IN CENTER AND EXTREME POS. (OPP. KEYWAY)</p>	<p>"L"</p>  <p>LOCKED OUT OF EXTREME POS. (KEYWAY SIDE)</p>	<p>"M"</p>  <p>LOCKED OUT OF AND INTO EXTREME POS. (OPP. KEYWAY)</p>	<p>"N"</p>  <p>LOCKED OUT OF EXTREME POS. (OPP. KEYWAY)</p>
<p>"P"</p>  <p>LOCKED OUT OF AND INTO EXTREME POS. (KEYWAY SIDE)</p>					

WASHER, LOCK (3)

WASHER, KEY (3)

2X NUT, PLAIN (3)

NOTES

- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- 2 - MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH
- 3 - FURNISHED UNASSEMBLED
- 4 - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS
- 5 - APPLIES ONLY TO "ON" AND "MOMENTARY ON" POSITIONS
- 6 - FROM BOTTOM OF KEYWAY TO MAJOR Ø OF 15/32 THREAD
- 7 - KEYWAY SHOWN ON LEFT SIDE
- 8 - YELLOW COATED LEVER
- 9 - NO QUICK CONNECT TERMINAL ASSEMBLY

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.


MICRO SWITCH
a Honeywell Division

FED MEG CODE 81839

SWITCH - TOGGLE

CATALOG LISTING
32NT291
SERIES CHART 2

THIRD ANGLE PROJECTION



SCALE	FULL
-------	------

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) $\pm .030$

TWO PLACES (.001) \pm 0.15

TWO PLACES	(.00)	±.015
THREE PLACES	(.000)	±.005

THREE PLACES (.000) $\pm .005$

ANGLES
WEIGHT .15 LBS APPROX