



POLARIZATION OPTION "A"
PN/ 34773-0140



POLARIZATION OPTION "B"
PN/ 34773-0141



POLARIZATION OPTION "C"
PN/ 34773-0142

MATERIAL NUMBER		CKT SIZE	DESCRIPTION	POL	COLOR
TRAY PACKAGING PK-31300-892	TUBE PACKAGING PK-31301-063				
34773-0140	34773-9140	14	STAC64 RIGHT ANGLE HEADER ASSEMBLY	A	BLACK
34773-0141	34773-9141	14	STAC64 RIGHT ANGLE HEADER ASSEMBLY	B	GREY
34773-0142	34773-9142	14	STAC64 RIGHT ANGLE HEADER ASSEMBLY	C	BROWN

NOTES: VALID UNLESS OTHERWISE SPECIFIED
1. GENERAL:

a. CONNECTOR HEADER MUST BE VALIDATED TO THE FOLLOWING
FUNCTIONAL REQUIREMENTS:

PIN RETENTION = USCAR-2 REV 5

SOLDERABILITY = SMES-152

b. APPLICATION REQUIREMENTS (REFERENCE ONLY) FOR:

SEE APPLICATION SPECIFICATION = TBD

SEE PRODUCT SPECIFICATION = TBD

MATES WITH: 34776-014w/34916-014w/34927-014w/34969-014w

c. PACKAGING SPECIFICATION SEE CHART.

2. DESIGN: MATERIALS:

a. SHROUD (PLASTIC HOUSING):
RESIN - SPS 30%GF

b. 0.4mm BLADES:
BASE MATERIAL: C26000
PLATING TYPE: AS NOTED

2.80mm BLADES:
BASE MATERIAL: C19400
PLATING TYPE: AS NOTED

c. PIN ALIGNMENT PLATE : MYLAR

3. PLATING REQUIREMENTS:

a. UNDERPLATING - OVERALL NICKEL

b. OVERPLATING - OVERALL TIN

ENTER DESCRIPTION IEC NO: UAU2014-0236 DRAWN BY: LSONG05 2011/01/13 CHECKED BY: YDANIELE 2011/01/13 APPROVED BY: SMARCEAU 2011/01/28 DATE: 2012/01/11	QUALITY SYMBOLS ∇=0 ∇=0 ∇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		4 PLACES ± 0.15 ± 0.25 3 PLACES ± 0.13 ± 0.25 2 PLACES ± 0.13 ± 0.25 1 PLACE ± 0.25 ± 0.25 0 PLACE ± 0.25 ± 0.25	mm INCH	DRAWN BY LSONG05	DATE 2011/01/13	TITLE STAC64 SINGLE BAY RIGHT ANGLE ASSEMBLY 14 CKT HYBRID			
		ANGULAR ± 3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY SMARCEAU	DATE 2011/01/28	molex			
		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-34773-010		SHEET NO. 1 OF 2			

