



Full metal top and side entry hoods
with different screw options

Identification	No. of contacts	Part No.	Drawing	Dimensions in mm																																				
40° side entry hood																																								
with internal grounding block	9	61 03 001		013																																				
	15	61 03 001		014																																				
	25	61 03 001		015																																				
without internal grounding block	9	61 03 001		013 010																																				
<table><tr><th>No. of contacts</th><th>A</th><th>B</th><th>C</th><th>D</th></tr><tr><td>9</td><td>31.0</td><td>25.0</td><td>35.0</td><td>15.0</td></tr><tr><td>15</td><td>39.3</td><td>33.3</td><td>35.0</td><td>15.0</td></tr><tr><td>25</td><td>53.0</td><td>47.0</td><td>35.0</td><td>15.0</td></tr></table>					No. of contacts	A	B	C	D	9	31.0	25.0	35.0	15.0	15	39.3	33.3	35.0	15.0	25	53.0	47.0	35.0	15.0																
No. of contacts	A	B	C	D																																				
9	31.0	25.0	35.0	15.0																																				
15	39.3	33.3	35.0	15.0																																				
25	53.0	47.0	35.0	15.0																																				
Top/side entry hood																																								
with internal grounding block	9	61 03 001		010																																				
	15	61 03 001		016																																				
	25	61 03 001		017 ¹⁾																																				
	37	61 03 001		018 ¹⁾																																				
	50	61 03 001		019 ¹⁾																																				
without internal grounding block	9	61 03 001		010 010																																				
<table><tr><th>No. of contacts</th><th>No. of cable entries</th><th>A</th><th>B</th><th>C</th><th>D</th></tr><tr><td>9</td><td>1 (top)</td><td>31.0</td><td>25.0</td><td>38.0</td><td>15.0</td></tr><tr><td>15</td><td>1 (top)</td><td>39.5</td><td>33.3</td><td>35.0</td><td>15.0</td></tr><tr><td>25</td><td>3</td><td>53.0</td><td>47.0</td><td>43.0</td><td>15.0</td></tr><tr><td>37</td><td>3</td><td>69.5</td><td>63.5</td><td>43.0</td><td>15.0</td></tr><tr><td>50</td><td>3</td><td>67.2</td><td>61.6</td><td>43.0</td><td>17.8</td></tr></table>					No. of contacts	No. of cable entries	A	B	C	D	9	1 (top)	31.0	25.0	38.0	15.0	15	1 (top)	39.5	33.3	35.0	15.0	25	3	53.0	47.0	43.0	15.0	37	3	69.5	63.5	43.0	15.0	50	3	67.2	61.6	43.0	17.8
No. of contacts	No. of cable entries	A	B	C	D																																			
9	1 (top)	31.0	25.0	38.0	15.0																																			
15	1 (top)	39.5	33.3	35.0	15.0																																			
25	3	53.0	47.0	43.0	15.0																																			
37	3	69.5	63.5	43.0	15.0																																			
50	3	67.2	61.6	43.0	17.8																																			
Please insert digit for screw option																																								
Knurled screw, thread 4-40 UNC	0																																							
Hexagonal screw, thread M3 with captive washer	1																																							
Hexagonal screw, thread 4-40 UNC with captive washer	2																																							
Knurled screw, thread M3	3																																							
Top entry hood for InduCom 9																																								
Hexagonal screw, thread 4-40 UNC	9	66 67 009 0346																																						
Hexagonal screw, thread M3	9	66 67 009 0347																																						
2 cable entries																																								

¹⁾ Part No. contains two blanking pieces
Operating temperature for all hoods on this page: -20 °C ... +90 °C