

**MICRO SWITCH**

FREEPORT, ILLINOIS, U.S.A.

A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

**ASSEMBLY-
PUSHBUTTON SWITCH**

CATALOG LISTING

3PB15-T**3PB15-T**

PAGE 1 OF 1

MDRAWING
NUMBER

11

ISSUE

REPLACES

RELEASE NO.

CHECK

REVISIONS

A

CO 19800

H B W

12 FEB 65

B

CO-

93593

P P F

27 OCT 98

C

CO-

94273

G J W

15 APR 99

JAF

CHECK

LSD

19 FEB 65

CHECK


H B W

12 FEB 65

DRAWN

FORMTEK

FO-50376

**NOTES**

- 1-UNIT INCLUDES "IISM" TYPE BASIC SWITCH (3)
- 2-TERMINALS ARE PLATED FOR SOLDERING
- 3-SWITCHES DO NOT NECESSARILY OPERATE SIMULTANEOUSLY
- 4-BASIC SWITCHES HAVE 24K SOLID GOLD CONTACTS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE ——— 35 OZ APPROX

TOTAL TRAVEL ——— .100 APPROX

ELECTRICAL DATACONTACT ARRANGEMENT
S P D T (3)

30 VOLTS DC RATING

INDUCTIVE ———	SEA LEVEL ———	1/2 AMP
	50,000 FT ———	1/2 AMP
RESISTIVE ———	SEA LEVEL ———	1 AMP
	50,000 FT ———	1 AMP
MAXIMUM INRUSH ———		2 AMP

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE
NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	±.030
TWO PLACE	(.00)	±.015
THREE PLACE	(.000)	±.005
ANGLES		±

WEIGHT