

Number of contacts

9–37

Mounting height



Standard Versions

SMC stamped solder pins, angled with grounding board locks

D-Sub

Performance levels

 Explanations see page 05.178
 Other performance levels on request


No. of contacts

Part No.

Performance level
3Performance level
2

Male connector

metal shell with dimples

2.84 mm pitch

2.84 mm pitch

9

09 65 167 781 . 1)

09 65 167 681 . 1)

15

09 65 267 781 . 1)

09 65 267 681 . 1)

25

09 65 367 781 . 1)

09 65 367 681 . 1)

37

09 65 467 781 . 1)

09 65 467 681 . 1)

2.54 mm pitch

2.54 mm pitch

9

09 65 166 781 .

09 65 166 681 .

15

09 65 266 781 .

09 65 266 681 .

25

09 65 366 781 .

09 65 366 681 .

37

09 65 466 781 .

09 65 466 681 .

Female connector

metal shell

2.84 mm pitch

2.84 mm pitch

9

09 66 157 761 . 1)

09 66 157 661 . 1)

15

09 66 257 761 . 1)

09 66 257 661 . 1)

25

09 66 357 761 . 1)

09 66 357 661 . 1)

37

09 66 457 761 . 1)

09 66 457 661 . 1)

2.54 mm pitch

2.54 mm pitch

9

09 66 156 761 .

09 66 156 661 .

15

09 66 256 761 .

09 66 256 661 .

25

09 66 356 761 .

09 66 356 661 .

37

09 66 456 761 .

09 66 456 661 .

Please insert digit for flange thread or fitted female screw locks

Ø 3.1 mm hole ▶ 0¹⁾

M3 ▶ 1

4-40 UNC ▶ 2

fitted screw locks 4-40 UNC ▶ 3