



Ethernet Media converter
Ha-VIS eCon 3011-ASFP
2-port Ethernet Media converter for vertical installation in control cabinets,
including 1 F.O. port (SFP)

Unmanaged	IP 30	PROFINET compatible 	EtherNet/IP compatible 
Number of ports, Copper / Termination		1x 10/100Base-T(X) / RJ45 (Twisted Pair) PoE support	
Number of ports, F.O. / Termination		1x 100Base-FX / SFP module slot	
mode PoE			
Input voltage / Termination		48 V DC	
Permissible range (min./max.)		46 V ... 57 V DC	
Input current		approx. 100 mA ... 400 mA at 48 V DC with PoE	
mode Non-PoE			
Input voltage / Termination		24 V DC / 5-pole, pluggable screw contact, redundant (PWR1 + / PWR1 - / PWR2 + / PWR2 - / FE)	
Permissible range (min./max.)		12 V ... 30 V DC	
Input current		approx. 100 mA (at 24 V DC)	
Housing material		metal, powder-coated	
Dimensions (W x H x D)		23 x 130 x 100 mm (without connectors)	
Weight		approx. 0.6 kg	
Working temperature		-40 °C ... +70 °C	
Approvals		cUL (in preparation)	
MTBF		2.090.000 h	

Identification	Part number	Drawing	Dimensions in mm
Ha-VIS eCon 3011-ASFP Ethernet Switch with 1 RJ45 port 1 F.O. port	20 76 102 3101		