

MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929




SWITCH - TOGGLE

4NT91 SERIES CHART 1


CATALOG LISTING


THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

CATALOG LISTING	CIRCUIT MADE WITH TOGGLE LEVER IN 			ELECTRICAL DATA
	KEYWAY SIDE (1-2, 4-5, 7-8, 10-11)	CENTER (1-2, 4-5, 7-8, 10-11)	OPPOSITE KEYWAY (2-3, 5-6, 8-9, 11-12)	
4NT91-1	ON	OFF	ON	L191 15A 125, 250, 277 VAC 1/2HP 125 VAC 1HP 250, 277 VAC 5A 125 VAC "L" 
(B)	OFF	NONE	ON	
4NT91-3	ON	NONE	ON	
(B)	NONE	OFF	ON	
(B)	NONE	ON	ON	
(B)	MOM OFF	NONE	ON	L192 10A 125, 250, 277 VAC 1/4HP 125 VAC, 1/2HP 250, 277 VAC 3A 125 VAC "L" 
4NT91-5	MOM ON	OFF	ON	
(B)	MOM ON	NONE	OFF	
4NT91-7	MOM ON	OFF	MOM ON	
(B)	MOM ON	NONE	ON	
(B)	NONE	ON	MOM ON	
(B)	MOM ON	OFF	NONE	



- NOTES
- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
 - 2 - MICRO SWITCH CATALOG LISTING MARKED ON SIDE OF SWITCH
 -  3 - FURNISHED UNASSEMBLED
 -  4 - APPLIES ONLY TO "ON" AND "MOM ON" POSITIONS



THIRD ANGLE PROJECTION	
	
SCALE	FULL
DO NOT SCALE PRINT	
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
ONE PLACE	(.0) ±.030
TWO PLACE	(.00) ±.015
THREE PLACE	(.000) ±.005
ANGLES	±
WEIGHT	