




PANEL CUTOUT
MAX. PANEL THICKNESS
14.0mm [.551]

SWITCH FUNCTION	
POS. 1	POS. 2
ON	(ON)
1-3	1-2

(ON) = MOMENTARY




SPDT
CONTACT CONFIGURATION


NOTE:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERMINAL NUMBERS FOR REF ONLY
- ▲ 4. CONTACT MATERIAL: SILVER
5. RATING: 2A 48VDC
6. ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
7. INSULATION RESISTANCE: 1,000 MΩ MIN.
8. DIELECTRIC STRENGTH: 2,000 VAC MIN. FOR 1 MINUTE
9. CONTACT RESISTANCE: 50mΩ MAX. @ 1A 12VDC
10. OPERATING TEMP.: -20°C to 55°C
11. ▲ DENOTES CRITICAL PARAMETER.
12. HARDWARE SUPPLIED: O-RING AND HEXNUT
- ▲ 13. INGRESS RATING: IP40
14. 2002/95/EC (ROHS) COMPLIANT

▲ BODY FINISH
BRUSHED STAINLESS
STEEL



1.50 [.059 in]
▲ ACTUATOR FINISH
BRUSHED STAINLESS
STEEL



TITLE PV3F2B0BB

SCALE 1.5:1

DATE 9/4/2012

DR RC

DWG 52-PV3F2B0BB

REV B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

B	20982	REMOVE UNUSED LAMP TERMINALS	1/22/13	EBP
A	20730	RELEASE FOR PRODUCTION	9/4/12	rc
REV	PCR NO	DESCRIPTION	DATE	BY