



Ethernet Switch
Ha-VIS eCon 4080-BPoE1
8-port Ethernet Switch for flat wall mounting, with Power over Ethernet

Unmanaged	IP 30	PROFINET compatible	EtherNet/IP compatible
-----------	-------	---------------------	------------------------

Number of ports, Copper / Termination	8x 10/100Base-T(X) / M12 D-coding PoE supports 8 ports
mode PoE	
Input voltage / Termination	48 V DC / M12 A-coding, male
Permissible range (min./max.)	46 V ... 55 V DC
Input current	max. 3 A at 46 V DC, load 350 mA per port
mode Non-PoE	
Input voltage / Termination	24 / 48 V DC / M12 A-coding, male, for redundant power supply
Permissible range (min./max.)	12 V ... 55 V DC
Input current	approx. 150 mA (at 24 V DC)
Housing material	metal, powder-coated
Dimensions (W x H x D)	130 x 166 x 50 mm (without connectors)
Weight	approx. 0.85 kg
Working temperature	-40 °C ... +70 °C
MTBF	505.000 h

Identification	Part number	Drawing	Dimensions in mm
----------------	-------------	---------	------------------

Ha-VIS eCon 4080-BPoE1 Ethernet Switch with 8 ports M12 D-coding for wall mounting	20 77 208 3009	
---	----------------	--