


D-SUB STANDARD – IP67

Solder cup – Precision machined contacts – Front mounting – For wire size AWG 20





RoHS compliant - CSA listed, File No.LR115000-1 UL listed, File No. E202784

SOCKET CONNECTOR





No. of pos.	A +0.2	B +0.2	C	D2 -0.25
09	21.10	39.40	25.00 +0.12 -0.10	16.46
15	21.10	47.70	33.30 +0.15 -0.10	24.79
25	21.10	61.40	47.04 +0.13	38.50
37	21.10	77.90	63.50 +0.13	54.96
50	23.90	75.50	61.10 +0.14 -0.11	52.55

Mounting style: Front spacer



Mounting style: Front spacer and rear mounting stud




ORDER DATA

SOCKET CONNECTOR		
No. of pos.	Mounting style	Part Number
09	M3 Front spacer	6 STD09SAM99B40 X
15	M3 Front spacer	6 STD15SAM99B40 X
25	M3 Front spacer	6 STD25SAM99B40 X
37	M3 Front spacer	6 STD37SAM99B40 X
50	M3 Front spacer	6 STD50SAM99B40 X
09	4-40 UNC Front spacer	6 STD09SAM99B50 X
15	4-40 UNC Front spacer	6 STD15SAM99B50 X
25	4-40 UNC Front spacer	6 STD25SAM99B50 X
37	4-40 UNC Front spacer	6 STD37SAM99B50 X
50	4-40 UNC Front spacer	6 STD50SAM99B50 X
09	4-40 UNC Front spacer and rear mounting stud	6 STD09SAM99B70 X
15	4-40 UNC Front spacer and rear mounting stud	6 STD15SAM99B70 X
25	4-40 UNC Front spacer and rear mounting stud	6 STD25SAM99B70 X
37	4-40 UNC Front spacer and rear mounting stud	6 STD37SAM99B70 X
50	4-40 UNC Front spacer and rear mounting stud	6 STD50SAM99B70 X

DESCRIPTION



- Suitable for wire size **AWG 20**
- Mounting styles:
 - with M3 or 4-40 UNC front spacer
 - with M3 or 4-40 UNC front spacer and rear mounting stud
- Quality class 3 (also available in quality class 1)
- Shell: Brass tin plated (stainless steel available on request)
- Nickel plated die-cast frame (Black plastic frame on request)

PLUG CONNECTOR





No. of pos.	A +0.2	B +0.2	C	D1 +0.25	E -0.30
9	21.10	39.40	25.00 +0.12 -0.10	16.79	5.82
15	21.10	47.70	33.30 +0.15 -0.10	25.12	5.82
25	21.10	61.40	47.04 +0.13	38.84	5.69
37	21.10	77.90	63.50 +0.13	55.30	5.69
50	23.90	75.50	61.10 +0.14 -0.11	52.68	5.69

Mounting style: Front spacer



Mounting style: Front spacer and rear mounting stud



PLUG CONNECTOR		
No. of pos.	Mounting style	Part Number
09	M3 Front spacer	6 STD09PAM99B40 X
15	M3 Front spacer	6 STD15PAM99B40 X
25	M3 Front spacer	6 STD25PAM99B40 X
37	M3 Front spacer	6 STD37PAM99B40 X
50	M3 Front spacer	6 STD50PAM99B40 X
09	4-40 UNC Front spacer	6 STD09PAM99B50 X
15	4-40 UNC Front spacer	6 STD15PAM99B50 X
25	4-40 UNC Front spacer	6 STD25PAM99B50 X
37	4-40 UNC Front spacer	6 STD37PAM99B50 X
50	4-40 UNC Front spacer	6 STD50PAM99B50 X
09	4-40 UNC Front spacer and rear mounting stud	6 STD09PAM99B70 X
15	4-40 UNC Front spacer and rear mounting stud	6 STD15PAM99B70 X
25	4-40 UNC Front spacer and rear mounting stud	6 STD25PAM99B70 X
37	4-40 UNC Front spacer and rear mounting stud	6 STD37PAM99B70 X
50	4-40 UNC Front spacer and rear mounting stud	6 STD50PAM99B70 X