



注記  
NOTES

- 材質  
MATERIAL  
ハウジング: ガラス入りPBT UL94V-0グレー  
HOUSING: PBT, G.F. UL94V-0  
ターミナル: 黄銅  
TERMINAL: BRASS
- メッキ仕様  
PLATING  
金メッキ: 0.1µm MIN.(接点部)  
GOLD: 0.1µm MIN.(CONTACT AREA)  
錫メッキ: 1.0µm MIN.(リセプタクル嵌合部)  
TIN: 1.0µm MIN.(RECEPTACLE CONNECTED AREA)  
ニッケルメッキ: 2.0µm MIN.(下地メッキ)  
NICKEL: 2.0µm MIN.(UNDER PLATING)
- 適合プラグカバー  
APPLICABLE PLUG COVER  
COVER A: 55513-1605, 55513-1615, 55513-1625, 55513-1635  
COVER B: 55514-1605
- 適合リセプタクル: 54596-0810, 54596-0910  
APPLICABLE RECEPTACLE
- 本製品は 55516-1605 の鉛フリー品である。  
THIS PRODUCT IS LEAD FREE OF 55516-1605.

DO NOT SCALE DRAWING

EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. J2004-4286 DRWN: M.NABEI '04/05/18 CHK: K.TOJO APPR: M.SASAO	RELEASSED	MATERIAL 材料 注記参照 SEE NOTES	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	SCALE 2-1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION	55516-1609	55516-160*
						FINISH 仕上げ 注記参照 SEE NOTES	10 UNDER 未満	±0.2	DRAWN BY & DATE M.NABEI '04/05/18	TITLE: SMALL-MGC PLUG INNER HS'G ASS'Y -LEAD FREE-	MATERIAL NO.	MODEL NO.
						WIRE RANGE 適用電線範囲	10 OVER 30 UNDER 未満	±0.25	CHECKED BY & DATE K.TOJO '04/05/18	<input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY	SHT	REV
						INS. RANGE 被覆外径	30 OVER 以上	±0.3	APPROVED BY & DATE M.SASAO '04/05/18	MOLEX INCORPORATED	REVISE ON CAD ONLY	
							ANGLE 角度	±3°	CAD FILENAME SD-55516-005.S01	MATERIAL NO. SEE CHART	DRAWING NO. SD-55516-005	SHEET NO. 1 OF 1
									THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.			SIZE B