

1	2	3	4	5
---	---	---	---	---

PCB LAYOUT - COMPONENT VIEW

TECHNICAL CHARACTERISTICS

MATERIAL

INSULATOR MATERIAL: PBT

FLAMMABILITY RATING UL94-V0

COLOUR: WHITE

CONTACT MATERIAL: COPPER ALLOY

CONTACT TYPE: STAMPED

CONTACT PLATING: SELECTIVE GOLD

SHIELDING: BRASS NI PLATED

QUALITY CLASS: 1500 MATING CYCLES

ENVIRONMENTAL

OPERATING TEMPERATURE: -40 °C UP TO 105 °C

COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL

CURRENT RATING: 1.5A Max

WORKING VOLTAGE: 30 V

INSULATION RESISTANCE: >1000 MOHM

DIELECTRIC WITHSTANDING VOLTAGE: 750 VAC/MN

CONTACT RESISTANCE: 20 mOHM MAX

STANDARD

CERTIFIED: E323964 / MODEL NUMBER 61400413321

SOLDERING

WAVE PROCESS ONLY

PACKAGING

TRAY

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = $\pm$ 0.2 .XX = $\pm$ 0.15			
K	21-AUG-13	DIM UPDATE	QL	APPROVAL: RJ		DESCRIPTION: USB 2.0 TYPE B VERTICAL		SIZE A4
J	21-AUG-13	DIM UPDATE	QL		UNIT: MM			
I	15-FEV-13	DESIGNATION	AR		SCALE:			
H	08-NOV-11	CURRENT RATING	GG		SHEET: 1/1	WERI PART NO: 61400413321		
REV	DATE	FILE	BY		DRAW:			