



| |

|

4G01P1 GIGABIT MAGNETIC CIRCUIT 

8. THE PART IS RECOMMENDED FOR WAVE SOLDERING PROCESS,
PREHEAT TEMPERATURE IS 120°C TO 160°C, 120 SECONDS TO 180 SECONDS,
PEAK SOLDERING TEMPERATURE IS 260 °C MAX, 10 SECONDS MAX.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN L VARELA - DOCKS GRC D. FAROLE APD D. FAROLE		 TRP connector Dongguan China	
DIMENSIONS: INCHES		TOLERANCES, UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± .010 2 PLC ± .005 4 PLC ± - 4 ANGLER ± -		NAME 1X1 MAG45(TM), MODULAR JACK, 4G1P1 GIGABIT SCHEMATIC, 4G01P1 MAGNETIC CIRCUIT (1 PIN HORIZ) SHIELDED, WITH BI-COLOR LEDS	
		PRODUCT SPEC 108-2100 APPLICATION SPEC -		SIZE A1	
MATERIAL 		FINISH 		DATE CODE C-6605463	
		WEIGHT -		RESTRICTED TO	
		CUSTOMER DRAWING		SCALE NTS SHEET 1 OF 1 REV F	