



Female connectors, straight

Identification	Number of contacts	Part No.				Dimensions in mm					
Female connector, straight, stacking heights 6.25 / 9.05 mm	6	15 2 .	006 .	601 .	...	A	B	C	D	E	G
	8	15 2 .	008 .	601 .	...	2.54	6.96	8.89	5.56	4.56	1.19
	10	15 2 .	010 .	601 .	...	3.81	8.23	10.16	6.83	5.83	1.19
	12	15 2 .	012 .	601 .	...	5.08	9.50	11.43	8.10	7.10	2.46
	14	15 2 .	014 .	601 .	...	6.35	10.77	12.70	9.37	8.37	2.46
	16	15 2 .	016 .	601 .	...	7.62	12.04	13.97	10.64	9.64	3.73
	18	15 2 .	018 .	601 .	...	8.89	13.31	15.24	11.91	10.91	3.73
	20	15 2 .	020 .	601 .	...	10.16	14.58	16.51	13.18	12.18	5.00
	22	15 2 .	022 .	601 .	...	11.43	15.85	17.78	14.45	13.45	5.00
	24	15 2 .	024 .	601 .	...	12.70	17.12	19.05	15.72	14.72	6.27
	26	15 2 .	026 .	601 .	...	13.97	18.39	20.32	16.99	15.99	6.27
	28	15 2 .	028 .	601 .	...	15.24	19.66	21.59	18.26	17.26	7.54
	30	15 2 .	030 .	601 .	...	16.51	20.93	22.86	19.53	18.53	7.54
	32	15 2 .	032 .	601 .	...	17.78	22.20	24.13	20.80	19.80	8.81
	34	15 2 .	034 .	601 .	...	19.05	23.47	25.40	22.07	21.07	8.81
	36	15 2 .	036 .	601 .	...	20.32	24.74	26.67	23.34	22.34	10.08
	38	15 2 .	038 .	601 .	...	21.59	26.01	27.94	24.61	23.61	10.08
	40	15 2 .	040 .	601 .	...	22.86	27.28	29.21	25.88	24.88	11.35
	42	15 2 .	042 .	601 .	...	24.13	28.55	30.48	27.15	26.15	11.35
	44	15 2 .	044 .	601 .	...	25.40	29.82	31.75	28.42	27.42	12.62
	46	15 2 .	046 .	601 .	...	26.67	31.09	33.02	29.69	28.69	12.62
	48	15 2 .	048 .	601 .	...	27.94	32.36	34.29	30.96	29.96	13.89
	50	15 2 .	050 .	601 .	...	29.21	33.63	35.56	32.23	31.23	13.89
	52	15 2 .	052 .	601 .	...	30.48	34.90	36.83	33.50	32.50	15.16
	54	15 2 .	054 .	601 .	...	31.75	36.17	38.10	34.77	33.77	15.16
	56	15 2 .	056 .	601 .	...	33.02	37.44	39.37	36.04	35.04	16.43
	58	15 2 .	058 .	601 .	...	34.29	38.71	40.64	37.31	36.31	16.43
	60	15 2 .	060 .	601 .	...	35.56	39.98	41.91	38.58	37.58	17.70
	62	15 2 .	062 .	601 .	...	36.83	41.25	43.18	39.85	38.85	17.70
	64	15 2 .	064 .	601 .	...	38.10	42.52	44.45	41.12	40.12	18.97
	66	15 2 .	066 .	601 .	...	39.37	43.79	45.72	42.39	41.39	18.97
	68	15 2 .	068 .	601 .	...	40.64	45.06	46.99	43.66	42.66	20.24
	70	15 2 .	070 .	601 .	...	41.91	46.33	48.26	44.93	43.93	20.24
	72	15 2 .	072 .	601 .	...	43.18	47.60	49.53	46.20	45.20	21.51
	74	15 2 .	074 .	601 .	...	44.45	48.87	50.80	47.47	46.47	21.51
	76	15 2 .	076 .	601 .	...	45.72	50.14	52.07	48.74	47.74	22.78
	78	15 2 .	078 .	601 .	...	46.99	51.41	53.34	50.01	49.01	22.78
	80	15 2 .	080 .	601 .	...	48.26	52.68	54.61	51.28	50.28	24.05
	82	15 2 .	082 .	601 .	...	49.53	53.95	55.88	52.55	51.55	24.05
	84	15 2 .	084 .	601 .	...	50.80	55.22	57.15	53.82	52.82	25.32
	86	15 2 .	086 .	601 .	...	52.07	56.49	58.42	55.09	54.09	25.32
	88	15 2 .	088 .	601 .	...	53.34	57.76	59.69	56.36	55.36	26.59
	90	15 2 .	090 .	601 .	...	54.61	59.03	60.96	57.63	56.63	26.59
	92	15 2 .	092 .	601 .	...	55.88	60.30	62.23	58.90	57.90	27.86
	94	15 2 .	094 .	601 .	...	57.15	61.57	63.50	60.17	59.17	27.86
	96	15 2 .	096 .	601 .	...	58.42	62.84	64.77	61.44	60.44	29.13
	98	15 2 .	098 .	601 .	...	59.69	64.11	66.04	62.71	61.71	29.13
	100	15 2 .	100 .	601 .	...	60.96	65.38	67.31	63.98	62.98	30.40
						62.23	66.65	68.58	65.25	64.25	30.40

Please insert digit for stacking height

6.25 mm ► 1
9.05 mm ► 2

for performance level 1
for performance level S4
for performance level 2

2
5
6

333
000

for samples
for 280 pieces on reel