






NOTE:

1. TEST:DC 300V/1s
2. INSULATION RESISTANCE:10m ohm
3. CONTACT RESISTANCE:2 ohm
4. PRODUCTS MEASURE UP TO THE ROHS
5. PVC TEGMENT

9	PE BAG 6'x9'x0.04MM	1PCS
8	ELLIPTICAL CABLE TIE WITH CORE L=70MM	1PCS
7	TIN WIRE LEAD-FREE Ø0.6 ROHS	0.45g
6	P1&P2 PVC , BLACK 45P	10g
5	CONDUCTIVE COPPER PLATINUM P1& P2.W:20MM*L:35MM	2PCS
4	GUMMED PAPER W:15MM	0.07m
3	PE1&P2 TRANSPARENT PE INTERNAL MODEL MATERIALS,LOW DENSITY	4g
2	HDMI C TYPE MALE: SHORT BODY PIN G/F,IRON SHELL-PLATED NICKEL,INSULATION BLACK	2PCS
1	UL20276[30AWG(7/0.10TS)*1P+E+AL/M]*4+30AWG(7/0.10TS)*1P+30AWG(7/0.10TS)*5C+A+EB(16/6/0.12AM) OD:6.0mm PVC BLACK TEGUMENT CUT L=990±10mm(LS)	1PCS
No	DESCRIPTION	QTY



-TOLERANCES- UNLESS OTHERWISE SPECIFIED		CnC Tech, LLC						
公差參考表				TITLE: HDMI CM TO CM CABLE PVC				
X.X ±0.38	X.X° ±3.00°	APPD: PRODUCT NO: 742-20010-00500						
X.XX ±0.25	X.XX° ±2.00°	CHECK:		DATE	SCALE	UNIT	TYPE	PAGE
X.XXX ±0.10	X.XXX° ±1.00°	DRAW:		2013.08.20	1:1	mm	Z	1 / 1

CnC Tech, LLC