

MICRO SWITCHFREEPORT ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL INC.
FED. MFG. CODE 91929**ACTUATOR-SWITCH**

CATALOG LISTING

8AS245-V3**8AS245-V3****M**DRAWING
NUMBER

5

ISSUE

REPLACES

RELEASE NO. PR-16430

CHECK

REVISIONS

A PR-16430

J A P

18 MAY 88

CHECK

18 MAY 88

CHECK


18 MAY 88

CHECK

18 MAY 88

CHECK


18 MAY 88

**NOTES**

- 1 - SCREWS, NUTS, AND LOCKWASHERS ARE FURNISHED ASSEMBLED
- 2 - LEVER AND BRACKET TYPE 302 CORROSION RESISTANT STEEL
- 3 - BASIC "V3-1001" (MS25253-1) AND JV-220 ACTUATOR ASSEMBLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH. A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

**CHARACTERISTICS**

OPERATING FORCE ----- 5 OZ MAX

RELEASE FORCE ----- 1 OZ MIN

PRETRAVEL ----- .188 MAX

DIFFERENTIAL TRAVEL ----- .078 MAX

OVERTRAVEL ----- .062 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P D T

15.1A 1/2HP 125 OR 250 VAC
1/2A 125 VDC, 1/4A 250 VDC
5A 125 VAC "L"

SCALE FULL

DO NOT
SCALE PRINTUNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) ± .030

TWO PLACE (.00) ± .015

THREE PLACE (.000) ± .005

ANGLES ± 1°

RAW MATERIAL - COMMERCIAL STANDARD

DIMENSIONS ARE IN INCHES AND ARE
TO BE MET BEFORE PROTECTIVE
COATINGS ARE APPLIED

MICRO SWITCH STANDARDS APPLY

WEIGHT

FO-52848-B

DRAWN

J A P 17 MAY 88