


NOTES:

- FOR USE WITH STRANDED COPPER WIRE ONLY
(SEE TABLE FOR WIRE RANGE)
- MATERIAL:
 - TERMINAL - CDA 260 BRASS, NICKEL PLATED
 - HOUSING - TYPE 66 NYLON
 - INSULATOR - HEAT SHRINKABLE POLYOLEFIN WITH HOT MELT SEALANT
- MINIMUM SHRINK TEMPERATURE: 300°F (150°C)
- ALL DIMENSIONS SHOWN ARE NOMINAL.
DIMENSIONS IN BRACKETS ARE IN MILLIMETERS.
- INSTALLATION TOOL: CT-310
- PACKAGING QTY:
 - STD PKG -Q = 25
 - BULK PKG. -D = 500

PART NUMBER		TAB SIZE	WIRE RANGE AWG	HOUSING COLOR	MAX. INSUL. DIA	DIMENSIONS			
PREFIX	PKG					A	W	H	L
DNH18-250FIM	-Q	.250 X .032 (6.35 X 0.81)	22-18	RED	.133 (3.38)	.90 (22.9)	.41 (10.4)	.31 (7.9)	1.50 (38.1)
DNH14-250FIM	-Q -D	.250 X .032 (6.35 X 0.81)	16-14	BLUE	.158 (4.01)	.90 (22.9)	.41 (10.4)	.31 (7.9)	1.50 (38.1)

A41457_03

03	7/03	KLFU		ADDED INTERNAL SERRATIONS				 TINLEY PARK, ILLINOIS	
02	7/01	JAMRLS		ADDED PACKAGE QTY. -Q & -D TO TABLE AND NOTES.	09505	TRO	JAC		
01	5/99	JKDRLS		MATERIAL WAS TIN PLATED	07642	KS	LCA		
00	12/90	DL	RLS	RELEASED	00221	KS	LCA		
REV	DATE	BY	CHK	DESCRIPTION	ECN	PM	CUST	DRAWN BY DRL	CHK'D LCA SCALE NONE DRAWING NO. A41457