

	1	2	3	4	5	6	7																																																																																											
A								A																																																																																										
B								B																																																																																										
C								C																																																																																										
D								D																																																																																										
E	Material: - Insulator: Glass-Filled Thermoplastic - PBT, UL94V-0 rated - Contact: Brass - Contact Plating: Gold flash full gold - Shell: Steel, 100µ" min. Nickel plated - Insulator color: Black - Clinch Nut: Brass, 100µ" min. Nickel plated - Boardlock: Brass, 100µ" min. Tin plated - Grounding hook boardlock +2 prong - Flange Mount: #4-40 threaded hole - Screwlock: Brass, 100µ" min. Nickel plated Electrical: - Contact Resistance: 20mΩ - Max at 1A DC - Insulation Resistance: 1,000MΩ @500VDC - Dielectric Withstanding Voltage: 1,000V AC/rms 60Hz for 1 minute - Current Rating: 3A - Voltage Rating: 250V AC/rms 60Hz							E																																																																																										
F	Dimensions <table border="1"> <thead> <tr> <th>Positions</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> <th>G</th> <th>H</th> </tr> </thead> <tbody> <tr> <td>15</td> <td>30.81</td> <td>24.99</td> <td>16.92</td> <td>16.33</td> <td>2.29</td> <td>1.145</td> <td>7.04</td> </tr> <tr> <td>26</td> <td>39.20</td> <td>33.30</td> <td>25.25</td> <td>24.70</td> <td>2.29</td> <td>1.145</td> <td>6.88</td> </tr> <tr> <td>44</td> <td>53.05</td> <td>47.04</td> <td>38.96</td> <td>38.40</td> <td>2.29</td> <td>1.145</td> <td>6.88</td> </tr> <tr> <td>62</td> <td>69.40</td> <td>63.50</td> <td>55.42</td> <td>54.80</td> <td>2.41</td> <td>1.205</td> <td>7.00</td> </tr> </tbody> </table> Order Code: AHDxxxA-KG-TAxB-R Male(S) or Female(F) Order pin number: 15,26,44,62 #4-40 UNC Hex stand offs (S) or without (X)							Positions	A	B	C	D	E	G	H	15	30.81	24.99	16.92	16.33	2.29	1.145	7.04	26	39.20	33.30	25.25	24.70	2.29	1.145	6.88	44	53.05	47.04	38.96	38.40	2.29	1.145	6.88	62	69.40	63.50	55.42	54.80	2.41	1.205	7.00	F																																																		
Positions	A	B	C	D	E	G	H																																																																																											
15	30.81	24.99	16.92	16.33	2.29	1.145	7.04																																																																																											
26	39.20	33.30	25.25	24.70	2.29	1.145	6.88																																																																																											
44	53.05	47.04	38.96	38.40	2.29	1.145	6.88																																																																																											
62	69.40	63.50	55.42	54.80	2.41	1.205	7.00																																																																																											
G	Unit: mm RoHS Compliant <table border="1"> <thead> <tr> <th>Scale</th> <th>1:1</th> <th></th> <th></th> <th></th> <th></th> <th>Date</th> <th>Name</th> <th>Title</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>11.03.13</td> <td>Wilson</td> <td>High Density DSub Connectors Right Angle Shrouded, M/F, 15-62 pin</td> </tr> <tr> <td>X.</td> <td>±0.38</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>11.03.13</td> <td>Groll</td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.X</td> <td>±0.25</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>AHDxxxA-KG-TAxB-R</td> </tr> <tr> <td>X.XX</td> <td>±0.13</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.°</td> <td>±3°</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.X°</td> <td>±1.0°</td> <td>①</td> <td>Updated all information</td> <td>11.03.13</td> <td>Wilson</td> <td></td> <td></td> <td>rev01</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="2"> ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us </td> <td>Sheet</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1/1</td> </tr> </tbody> </table>							Scale	1:1					Date	Name	Title	TOLERANCE					Drawn	11.03.13	Wilson	High Density DSub Connectors Right Angle Shrouded, M/F, 15-62 pin	X.	±0.38				Approved	11.03.13	Groll	ASSMANN WSW-No.	X.X	±0.25							AHDxxxA-KG-TAxB-R	X.XX	±0.13							Drawing-No.	DIM	TOL								X.°	±3°								X.X°	±1.0°	①	Updated all information	11.03.13	Wilson			rev01	Angle	TOL	Id.	Modification	Date	Name	ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us		Sheet									1/1	G
Scale	1:1					Date	Name	Title																																																																																										
TOLERANCE					Drawn	11.03.13	Wilson	High Density DSub Connectors Right Angle Shrouded, M/F, 15-62 pin																																																																																										
X.	±0.38				Approved	11.03.13	Groll	ASSMANN WSW-No.																																																																																										
X.X	±0.25							AHDxxxA-KG-TAxB-R																																																																																										
X.XX	±0.13							Drawing-No.																																																																																										
DIM	TOL																																																																																																	
X.°	±3°																																																																																																	
X.X°	±1.0°	①	Updated all information	11.03.13	Wilson			rev01																																																																																										
Angle	TOL	Id.	Modification	Date	Name	ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us		Sheet																																																																																										
								1/1																																																																																										
H	1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us							H																																																																																										
	1	2	3	4	5	6	7																																																																																											