



Material:

- 1.Cable: UL2919, 3COAXIAL+7C+1+AL/MY+Braid,O.D:8.5
- 2.Connector: HD15M, 9th Empty, Black
HD15F, Black
- 3.Thumbscrew:#4-40UNC, E32
- 4.Black Heat Shrink:∅1.5x15:6PCS ∅3x8:6PCS
- 5.Copper Size:30X50

Note:

- 1.Total Length: SEE "ITEM NO."
- 2.Color: Beige
- 3.Molded Type
- 4.360° Solder

Configuration:

HD15M		HD15F
1	Red(Coax)	1
6	Red(Ground)	6
2	Green(Coax)	2
7	Green(Ground)	7
3	Blue(Coax)	3
8	Blue(Ground)	8
4	Brown	4
5	Black	5
13	Green	13
14	Red	14
10	Orange	10
11	White	11
12	Yellow	12
Shield	(Braid)	Shield



ITEM NO	AK3730X-R (3 Meters) AK3740X-R (5 Meters) AK3750X-R (10 Meters)
TITLE	PREMIUM XGA Monitor Extension Cable, HD DSUB 15-Pin Male to HD DSUB 15-Pin Female

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved