

	1	2	3	4	5	6	7																																																																																		
A								A																																																																																	
B								B																																																																																	
C								C																																																																																	
D								D																																																																																	
E	Material: - SVT 3x18AWG(0.824MM²) VW-1 Shielded, 105° 300V - Jacket Color: Black - E- Green; L- Black; N- White Electrical Test : 100% Open & Short Testing - Insulation Resistance : 100meg-ohm(Min.) - Voltage : 500V DC / 1 Min.							E																																																																																	
F								F																																																																																	
G	Unit: mm RoHS Compliant <table border="1"> <tr> <td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Title</td></tr> <tr> <td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>27.12.11</td><td>Chappell</td></tr> <tr> <td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td>Approved</td><td>21.06.13</td><td>Groll</td></tr> <tr> <td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr> <td>X.X°</td><td>±X°</td><td>①</td><td>Updated all information</td><td>21.06.13</td><td>Wilson</td><td></td><td></td><td></td></tr> <tr> <td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td></td><td></td><td></td></tr> </table> ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us Power cord - Plug ⇔ Open End SVT, 18AWG, 105°C, Shielded, 0.5 meter ASSMANN WSW-No. AK500-OE-7-0.5-R Drawing-No. rev01 Replace Sheet 1/1							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	27.12.11	Chappell	X.	±X					Approved	21.06.13	Groll	X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°	①	Updated all information	21.06.13	Wilson				Angle	TOL	Id.	Modification	Date	Name				G
Scale	Free					Date	Name	Title																																																																																	
TOLERANCE						Drawn	27.12.11	Chappell																																																																																	
X.	±X					Approved	21.06.13	Groll																																																																																	
X.X	±X																																																																																								
X.XX	±X																																																																																								
DIM	TOL																																																																																								
X.°	±X°																																																																																								
X.X°	±X°	①	Updated all information	21.06.13	Wilson																																																																																				
Angle	TOL	Id.	Modification	Date	Name																																																																																				
H								H																																																																																	
	1	2	3	4	5	6	7																																																																																		