

	1	2	3	4	5	6	7																																																									
A	Material Item 1 : Terminal housing:Thermoplastic (UL94V-0),Green Item 2 : Clamp: Brass , Ni plated Item 3 : Wire guard solder pin: Brass,Tin plated Item 4 : Terminal screw: Steel Zinc plating "-" slot type Electrical cULus Voltage rating: 300V Current rating: 20A Wire range: Solid wire(AWG) : 12-22 Stranded wire(AWG) : 12-22 Torque(L-b-In) : 3.5 Screw:M3 Wire strip length: 6-7mm Withstanding Voltage: 1.6kV/ Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval: CRAIUS DIMENSION L NX5.08P (N-1)x5.08 N=Number of poles<table><tr><th>Poles</th><th>Tolerance</th></tr><tr><td>DIM L</td><td>DIM P</td></tr><tr><td>2p-6p</td><td>±0.15</td></tr><tr><td>7p-12p</td><td>±0.25</td></tr><tr><td>13p-18p</td><td>±0.35</td></tr><tr><td>19p-24p</td><td>±0.40</td></tr></table> RECOMMENDER PCB LAYOUT							Poles	Tolerance	DIM L	DIM P	2p-6p	±0.15	7p-12p	±0.25	13p-18p	±0.35	19p-24p	±0.40																																													
Poles	Tolerance																																																															
DIM L	DIM P																																																															
2p-6p	±0.15																																																															
7p-12p	±0.25																																																															
13p-18p	±0.35																																																															
19p-24p	±0.40																																																															
B	Rohs compliant																																																															
G																																																																
H	<table><tr><th>Scale</th><th>1:1</th><th></th><th></th><th></th><th>Date</th><th>Name</th><th>Customer-No.</th></tr><tr><td>TOLERANCE</td><td>X.</td><td>±0.50</td><td></td><td></td><td>Drawn</td><td>06.12.2006</td><td>Helwig</td></tr><tr><td>X.X</td><td></td><td>±0.30</td><td></td><td></td><td>Approved</td><td>20.04.2010</td><td>Helwig</td></tr><tr><td>X.XX</td><td></td><td>±0.10</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td></td><td>TOL</td><td>① Update</td><td></td><td>20.04.2010</td><td>Alex</td><td></td></tr><tr><td>X.°</td><td></td><td>±1°</td><td>ⓐ Drawn</td><td></td><td>06.12.2006</td><td>Helwig</td><td></td></tr><tr><td>Angle</td><td></td><td>TOL</td><td></td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td></tr></table> components Drawing-No. ASS 0652 CO Replace Sheet							Scale	1:1				Date	Name	Customer-No.	TOLERANCE	X.	±0.50			Drawn	06.12.2006	Helwig	X.X		±0.30			Approved	20.04.2010	Helwig	X.XX		±0.10						DIM		TOL	① Update		20.04.2010	Alex		X.°		±1°	ⓐ Drawn		06.12.2006	Helwig		Angle		TOL		Id.	Modification	Date	Name	
Scale	1:1				Date	Name	Customer-No.																																																									
TOLERANCE	X.	±0.50			Drawn	06.12.2006	Helwig																																																									
X.X		±0.30			Approved	20.04.2010	Helwig																																																									
X.XX		±0.10																																																														
DIM		TOL	① Update		20.04.2010	Alex																																																										
X.°		±1°	ⓐ Drawn		06.12.2006	Helwig																																																										
Angle		TOL		Id.	Modification	Date	Name																																																									