



Material
 Item a Clamp : Brass(CuZn) Ni plated
 Item b Terminal screw: Steel Zinc plating "-" slot type
 Item c Female contact : PhBz(CuZn)Tin plated
 Item d Terminal housing: Thermoplastic (UL94V-0) ,Green

Electrical cULus
 Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 16-28
 Stranded wire(AWG): 16-28
 Torque(Lb-In): 1.7
 Screw: M2
 Wire strip length: 5-6mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Safety approval: cULus

DIMENSION

L	Nx3,5
P	(N-1)x3,5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
4p-6p	±0.15	±0.15
7p-12p	±0.20	±0.20
13p-24p	±0.30	±0.30

RoHS compliant

Scale	1:1	Date	30.11.2006	Name	Hellwig
TOLERANCE		Drawn	30.11.2006	Hellwig	
X.	±0.50	Approved	20.04.2010	Hellwig	
X.X	±0.30				
X.XX	±0.10				
DIM	TOL	Update	20.04.2010	Alex	
X.°	±1°	Drawn	30.11.2006	Hellwig	
Angle	TOL	Id.	Modification	Date	Name



Customer-No.	
ASSMANN WSW-No. A-TB350-THxx	
Drawing-No.	rev02
ASS 1150 CO	Sheet
Replace	

RoHS compliant