

	1	2	3	4	5	6	7																																																																																									
A	0,6 N x 7.5 0,6 19,0 4,0 7.50 (N-1) x 7.5 0,90 □ 2.95 x 3.8 P.C.B LAYOUT (4,35) (N-1) x 7.5 (4,35) (10,5) (5,0) Ø1,60 5,0 10,5 Material 1.Terminal body (metal housing): Brass(CuZn) 2.Terminal screw:Steel Zinc plating"-slot type 3.Contacts: Brass 4.Surface of solder tail: Tin plated 5.Insulator (housing): Thermoplastic (UL94V-0) Electrical 1.Voltage rating: 300VAC 2.Current rating: 20A 3.Solid wire(AWG): 12-30 4.Stranded wire(AWG): 12-30 5.Torque: 3.5 Lb-In 6.Screw:M3 7.Wire strip length:6-7mm 8.Withstanding Voltage: 1.6KV 9.Operating temperature: -30°C to +105°C 10.Soldering temperature: 250°C±10°C/5 Sec 11.Safety Approval: cULus							A																																																																																								
B								B																																																																																								
C								C																																																																																								
D								D																																																																																								
E								E																																																																																								
F								F																																																																																								
G	RoHS compliant <table><tr><td>Scale</td><td>1:1</td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Customer-No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>27.05.2009</td><td>Dean</td><td></td></tr><tr><td>X.</td><td>±0.50</td><td></td><td></td><td></td><td></td><td>Approved</td><td>27.05.2009</td><td>Hellwig</td><td>ASSMANN WSW-No. A-TB750-VJxxH</td></tr><tr><td>X.X</td><td>±0.30</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±0.10</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawing-No.</td></tr><tr><td>X.°</td><td>±1°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td>①</td><td>Drawn</td><td>27.05.2009</td><td>Dean</td><td colspan="2" rowspan="3"></td><td>ASS 3523 CO</td><td>rev01</td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td>Replace</td><td>Sheet</td></tr></table>							Scale	1:1						Date	Name	Customer-No.	TOLERANCE						Drawn	27.05.2009	Dean		X.	±0.50					Approved	27.05.2009	Hellwig	ASSMANN WSW-No. A-TB750-VJxxH	X.X	±0.30									X.XX	±0.10									DIM	TOL								Drawing-No.	X.°	±1°									X.X°	±X°	①	Drawn	27.05.2009	Dean			ASS 3523 CO	rev01	Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet	G
Scale	1:1						Date	Name	Customer-No.																																																																																							
TOLERANCE						Drawn	27.05.2009	Dean																																																																																								
X.	±0.50					Approved	27.05.2009	Hellwig	ASSMANN WSW-No. A-TB750-VJxxH																																																																																							
X.X	±0.30																																																																																															
X.XX	±0.10																																																																																															
DIM	TOL								Drawing-No.																																																																																							
X.°	±1°																																																																																															
X.X°	±X°	①	Drawn	27.05.2009	Dean			ASS 3523 CO	rev01																																																																																							
Angle	TOL	Id.	Modification	Date	Name			Replace	Sheet																																																																																							
H								H																																																																																								
	1	2	3	4	5	6	7	SV1501																																																																																								