



1 Material

- Item (a) Clamp: Brass(CuZn) Ni plated
- Item (b) Terminal screw :Steel Zinc plating"-slot type
- Item (c) Female contact: PhBz, Tin plated
- Item (d) Terminal(housing): Thermoplastic (UL94V-0) Green(RAL6018/T)
- Item (e) Terminal(cover): Thermoplastic (UL94V-0) Green(RAL6018/T)

Electrical cULus/VDE
 Voltage rating: 300VAC/300VAC
 Current rating: 10A/10,5A
 Wire range: 1.5mm²
 Solid wire(AWG): 16-28/16-28
 Stranded wire(AWG): 16-28/16-28
 Torque: 3Lb-In /0.2N.m
 Screw: M2
 Wire strip length: 6-7 mm
 Withstanding Voltage: 1.6KV/2.5KV
 Operating temperature: -40°C to +115°C
 Safety Approval:

1 Dimension

Dimension	Value
DIM A	Nx3,81
DIM B	(N-1)x3,81

N=Number of poles

Poles	Tolerance DIM A	Tolerance DIM B
2P-6P	±0.15	±0.15
7P-12P	±0.20	±0.20
13P-18P	±0.25	±0.25
19P-24P	±0.30	±0.30

RoHS compliant
Unit: mm

Scale	Free					Date	Name	Customer-No.
TOLERANCE						Drawn	10.12.2009	Dean
X.	±0.50					Approved	06.03.2013	Amy
X.X	±0.30							
X.XX	±0.10							
DIM	TOL							
X.°	±1°	②	Update	06.03.2013	Amy			
		①	Drawn	10.12.2009	Dean			
Angle	TOL	Id.	Modification	Date	Name	Replace		Sheet

ASSMANN WSW-No.
A-TB381-TJxxU

Drawing-No.
ASS 3832 CO rev02