

	1	2	3	4	5	6	7																																																																																									
A	P.C.B. LAYOUT ③ N x 5.08 + 2.54 ③ 14.2 1.3 7.62 0.50 14.2 1.3 7.62 0.50 N=Number of contacts Material Terminal body(contact pin): Brass Wire guard: Stainless steel Surface of solder tail: Tin plated Insulator(housing): Thermoplastic (UL94V-0),Green(RAL6018/T) Electrical cULus / VDE Voltage rating: 300VAC /250VAC Current rating: 10A/10A Wire range: 0.75-1.5MM² Solid wire(AWG): 14-24 Stranded wire (AWG): 14-24 Torque: Screw: ② Wire strip length: 9-10mm Withstanding Voltage: 1.6KV/2KV ② Operating temperature: -40°C to +115°C Soldering temperature: 250°C ± 10°C/5 Sec Safety Approval:							A																																																																																								
B								B																																																																																								
C								C																																																																																								
D								D																																																																																								
E								E																																																																																								
F								F																																																																																								
G	RoHS compliant Unit: mm <table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td colspan="2">Customer-No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawn</td><td>10.12.2009</td><td>Dean</td></tr><tr><td>X.</td><td>±0.50</td><td></td><td></td><td></td><td></td><td></td><td rowspan="2">Approved</td><td rowspan="2">01.04.2013</td><td rowspan="2">Amy</td><td rowspan="3">ASSMANN WSW-No. A-TB508-HAxxV</td></tr><tr><td>X.X</td><td>±0.30</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±0.10</td><td>③</td><td>Update</td><td></td><td>01.04.2013</td><td>Amy</td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td>②</td><td>Update drawing</td><td></td><td>16.09.2010</td><td>Rale</td><td colspan="3" rowspan="2"></td><td>Drawing-No.</td></tr><tr><td>X.°</td><td>±1°</td><td></td><td></td><td></td><td></td><td></td><td>ASS 3895 CO</td></tr><tr><td></td><td></td><td>①</td><td>Drawn</td><td></td><td>10.12.2009</td><td>Dean</td><td colspan="3" rowspan="3"></td><td>rev03</td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td></td><td>Date</td><td>Name</td><td>Replace</td><td>Sheet</td></tr></table>							Scale	Free						Date	Name	Customer-No.		TOLERANCE							Drawn	10.12.2009	Dean	X.	±0.50						Approved	01.04.2013	Amy	ASSMANN WSW-No. A-TB508-HAxxV	X.X	±0.30						X.XX	±0.10	③	Update		01.04.2013	Amy				DIM	TOL	②	Update drawing		16.09.2010	Rale				Drawing-No.	X.°	±1°						ASS 3895 CO			①	Drawn		10.12.2009	Dean				rev03	Angle	TOL	Id.	Modification		Date	Name	Replace	Sheet	G
Scale	Free						Date	Name	Customer-No.																																																																																							
TOLERANCE							Drawn	10.12.2009	Dean																																																																																							
X.	±0.50						Approved	01.04.2013	Amy	ASSMANN WSW-No. A-TB508-HAxxV																																																																																						
X.X	±0.30																																																																																															
X.XX	±0.10	③	Update		01.04.2013	Amy																																																																																										
DIM	TOL	②	Update drawing		16.09.2010	Rale				Drawing-No.																																																																																						
X.°	±1°									ASS 3895 CO																																																																																						
		①	Drawn		10.12.2009	Dean				rev03																																																																																						
Angle	TOL	Id.	Modification		Date	Name				Replace	Sheet																																																																																					
H										H																																																																																						
	1	2	3	4	5	6	7																																																																																									