





Extended length is with 500g of force

### Materials:

- Plug Housing: Polycarbonate, clear
- Plug Terminal: 0.36" [.014MM] Thick Phosphor Bronze
- Connector: 50μ" of Selective Gold Contact Plating
  - Area, Gold flash over the remainder
  - Over 2.54μm [.000100] thick nickel underplate
- Conductor(X4C): 26AWG (0.12X12) Bare Copper
- Insulation(X4C): PP6331 ID 0.95-1.0
- Jacket: PVC NOUL 80P
- Package: Individual PE Bag



SEC: A=A

| P1 | COLOR  |
|----|--------|
| 1  | WHITE  |
| 2  | BLACK  |
| 3  | RED    |
| 4  | GREEN  |
| 5  | YELLOW |
| 6  | BLUE   |

| Extended Length ("L2")      | Typical Retracted Length ("L1") |
|-----------------------------|---------------------------------|
| 120.0 Inches - 138.0 Inches | 39.5 Inches                     |
| 3,048.0MM-3,505.2MM         | 1,003.3MM                       |

**RoHS**  
Compliant

ITEM NO

**AT-C-26-6/6/S-10-OE-R**

TITLE NON-UL 26AWG (0.16/7)\*6C, O.D.: 2.4\*6.8MM

Single Plug, 50μ" of contact plating, SILVER

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED

© Copyright 2009 by Assmann Electronic Components  
All International Rights Reserved